

CASE NOTE

ACS1000 variable speed drive operates refiner in a pulp and paper mill



Horizon Pulp & Paper

Horizon Pulp & Paper is an independent, fully integrated pulp and paper mill located in Kehra, Estonia. The mill produces and exports sack kraft paper, sacks and a variety of tissue products. It is a member of the Tolaram Group, an international company with vastly diversified activities, including manufacturing of textiles, fibres and polymers and pulp and paper.

In 2001 Horizon invested in modernization of the Estonian paper mill. The site's recovery boiler, paper machine no. 1 and the refining system were upgraded.

High consistency refining system

In the paper production process, refiners separate wood fibers from wood chips. Thermo-mechanical pulping (TMP) with a pressurized refiner is a commonly used refining process.

At Horizon, the advanced high consistency (HC) refining is done with a RGP-250 refiner at a consistency of 30-33 percent. Depending on pulp characteristics and quality, the typical input is 300-380 kWh/t. Horizon Pulp & Paper produces and exports sack kraft paper, sacks and a variety of tissue products in Kehra, Estonia. As part of the modernization of Horizon's paper mill the refiner motor (3.5 MW) was upgraded with an ACS1000 variable speed drive. By controlling the refiner motor with ABB's ACS1000, the motor can be started without causing any voltage drops in the supply network.

Highlights

Start-up of refiner motor without voltage drop in supply network	
Minimized total investment	
Increased availability	
Reduced maintenance costs	
Extended lifetime of equipment	



ACS1000 water cooled

Challenge

In order to start the 3.5 MW medium voltage asynchronous refiner motor, certain requirements had to be met:

- Horizon had to be able to start up the refiner independent of the supply network's working parameters. In addition, the start of the asynchronous motor should not cause any disturbances in Horizon's existing automation equipment.
- Eesti Energia, the local electricity utility company, requested that voltage drops at 35 kV supply lines must not exceed four percent.

Solution

As neither direct-on-line (DOL) nor reactor start up met the requirements of both Horizon and Eesti Energia, Horizon decided to use a variable speed drive (VSD) to start the refiner motor.

The following criteria were taken into consideration:

- · Efficiency of the overall power chain
- Maintenance costs
- Availability

ABB was chosen as supplier for the HC refiner drive system due to the following advantages of ABB's ACS1000 medium voltage drive:

- High availability
- Minimum investment in other parts of the mill
- Short installation time
- Low operating and maintenance costs
- Output capacity

Benefits

Soft starting

During the starting process, the ACS1000 variable speed drive (VSD) progressively increases the motor speed and accelerates the load smoothly to its rated speed without causing torque or current peaks.

By operating the refiner motor with a VSD, the requirements of Horizon as well as the utility company are fulfilled and even exceeded. No disturbances are caused to Horizon's existing automation equipment and practically no voltage drop can be detected during refiner motor start at the 35 kV supply lines, even in weak power grid conditions.

Increased lifetime of equipment



Soft starting of the refiner decreases maintenance costs as stress on the motor and the refiner is reduced.

No need for power factor compensator



Due to the natural commutated diode

bridge, the power factor is independent of speed and load. The effective power factor

is equal or better than 0.95.

Direct Torque Control (DTC)



The ACS1000 motor control platform is based on DTC, which allows direct control of all core motor variables thus responding

to process changes extremely fast. Short supply voltage interruptions, from few cycles to few hundred milliseconds, will have no effect on the refiner drive system, due to the Power Loss Ride-Through function of the ACS1000.

High reliability & availability



The ACS1000 uses the IGCT (Integrated Gate Commutated Thyristor) power semiconductor as an integrated protection device. This leads to a lower parts count, making the ACS 1000 a drive with outstanding reliability

Customer satisfaction

and availability.

Horizon Pulp & Paper states: "We would like to thank ABB for their excellent work. The installed drive system fulfills all specified requirements and is running well with no problems."

ACS1000 key data	
Inverter type	Three-level Voltage Source Inverter (VSI)
Power range	Air-cooled: 315 kW-2 MW Water-cooled: 1.8 MW-5 MW
Output voltage	2.3 kV, 3.3 kV, 4.0 kV, 4.16 kV
Maximum output frequency	0 to 82.5 Hz (higher on request)
Converter efficiency	>98%, external transformer >96%, integrated transformer
Type of motor	Induction motor

3BHT490425R0001 REV B EN 19.12.2019

For more information please contact: abb.com/drives www.horizon.ee

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents - in whole or in parts - is forbidden without prior written consent of ABB. Copyright© 2019 ABB. All rights reserved.