

ATEX

Industrial plugs and sockets

Explosion proof



From great to EXplosive
We are strengthening the
great range of industrial plugs
and sockets from ABB with explosion proof IP&S products.

ATEX =
"ATmosphere EXplosive"
Gas explosion protection:
II 2 G Ex de IIC T6 Gb

ABBs range of industrial plugs and sockets covers most applications, with our Tough & Safe and heavy duty mechanical interlocks we have products for most harsh environments with chemicals, UV or mechanical wear. However, up until now we have not been able to offer ATEX approved explosion proof products. Now through this cooperation we will fill this gap and further strengthen our offering.

What is ATEX?

ATEX is a European Directive (94/9/EC) valid for products to be used within an explosive atmosphere. The ATEX directive has been in force throughout the European Union since 1 July 2003, replacing the existing different national and European legislation relating to explosive atmospheres.

Why ATEX?

An ambience with the potential to become an explosive atmosphere during operating conditions and/or under the influence of the environment is defined as a potentially explosive atmosphere. Products covered by directive 94/9/EC are defined as intended for use in potentially explosive atmospheres.

Directive 94/9/EC defines an explosive atmosphere as a mixture of:

- flammable substances gases, vapors, mists or dusts
- with air
- under specific atmospheric conditions
- in which, after ignition has occurred, combusti



Ordering detail

Application range (Zone): 1, 2, 21, 22









Terminals/ Poles	Voltage V	Frequency Hz	Туре	Order code	Pack qty
Mechanical inte	rlocked socket 16 A	, IP 66 . Dust explosion	n protection: II 2 D Ex tD A21 8	30ºC Db	
2P+E	200-250	50 and 60	216MVS6XW	2CMA101687R1000	1
3P+N+E	346-415	50 and 60	416MVS6XW	2CMA101688R1000	1
Mechanical inter	rlocked socket 32 A	, IP 66. Dust explosior	n protection: II 2 D Ex tD A21 7	5ºC	
3P+N+E	346-415	50 and 60	432MVS6XW	2CMA101689R1000	1
Mechanical inter	rlocked socket 63 A	, IP 66. Dust explosion	n protection: II 2 D Ex tD A21 6	0ºC	
3P+N+E	346-415	50 and 60	463MVS6XW	2CMA101690R1000	1
Mechanical inter	rlocked socket 125 /	A. Dust explosion pro	tection: II 2 D Ex tD A21 65ºC [Db	
3P+N+E	346-415	50 and 60	4125MVS6XW	2CMA101691R1000	1

Terminals/ Poles	Voltage V	Frequency Hz	Type	Order code	Pack qty
Plug 16 A, IP 66.	Dust explosion pro	tection: II 2 Ex tD A21	80°C Db		'
2P+E	200-250	50 and 60	216P6XW	2CMA101692R1000	1
3P+N+E	346-415	50 and 60	416P6XW	2CMA101693R1000	1
Plug 32 A, IP 66.	Dust explostion pro	otection: II 2 D Ex tD A	∆21 75ºC		
3P+N+E	346-415	50 and 60	432P6XW	2CMA101694R1000	1
Plug 63 A, IP 66.	Dust explosion pro	tection; II 2 D Ex tD A	21 60ºC		
3P+N+E	346-415	50 and 60	463P6XW	2CMA101695R1000	1
Plug 125 A, IP 66	. Dust explosion pr	otection; II 2 D Ex tD A	A2180ºC		
3P+N+E	346-415	50 and 60	4125P6XW	2CMA101696R1000	

ABB AB Electrification Products Division

Box 1005 SE-611 29 NYKÖPING, Sweden Phone: +46 155 29 50 00

www.abb.com/industrialplugs www.abb.com