


System software update on Jokab Safety Gateway.

- Start the Terminal Window under “Tools” menu. You will be prompted “pb_gw>” if you are using a Profibus gateway.
- Type the command boot and select the option m. This will reboot the gateway in monitor mode.



The screenshot shows a Windows-style terminal window titled "PlutoManager Terminal Window". The window has three buttons at the top: "Send File", "Close", and "Copy". The main text area displays the following information:

```
Serial number: 1002
*****
Software ver : 1.1.1
Software date: 2006-07-12
*****
(c) JOKAB SAFETY AB
*****
pb_gw> boot
Reboot all Plutos? (y/n/m) m

*****
* Pluto Gateway Boot-Loader *
* Vers 1.00 created 2005-10-14 *
* Serial No 0000001002 *
* Profibus *
* Hardware Ver 01 - 000000 *
* (c) Jokab Safety AB *
*****
OS ver:1.1.1

*****
* Pluto Gateway Boot-Loader *
* Vers 1.00 created 2005-10-14 *
* Serial No 0000001002 *
* Profibus *
* Hardware Ver 01 - 000000 *
* (c) Jokab Safety AB *
*****
OS ver:1.1.1

Pluto_GW>
```

- You will now be prompted Pluto_GW>
- Type the command sys and verify with y.
- The old system software will now be deleted and when ready, please start loading... shows you click on the “Send File” button. In the new window you need to brows to the gatewayProfibus_v1-1-2_2006-06-13.mhx file. When you select open the download will start.
- When the download is ready the system check sum must be written to the flash memory.

The screenshot shows the PlutoManager Terminal Window. The terminal window has a blue title bar with the text "PlutoManager Terminal Window". Below the title bar are three buttons: "Send File", "Close", and "Copy". The main window displays the following text:

```
* Pluto Gateway Boot-Loader      *
* Vers 1.00 created 2005-10-14 *
* Serial No 0000001002         *
* Profibus                      *
* Hardware Ver 01 - 000000      *
* (c) Jokab Safety AB          *
***** OS ver:1.1.1
***** OS ver:1.1.1
***** OS ver:1.1.1
Pluto_GW>sys - Load system flash, are you sure? (y/n) y Erase..  OK (1704 ms)
** Ready, please start loading... Load OK
Pluto_GW>cs - system rom CRC = 0xC7E8 Write CRC to flash (y/n)? y
Pluto_GW>
```

- Type the command cs and confirm with y.
- You can restart the gateway by switching the power off and on or type the command “boot”.

The screenshot shows the PlutoManager Terminal Window. The terminal window has a blue title bar with the text "PlutoManager Terminal Window". Below the title bar are three buttons: "Send File", "Close", and "Copy". The main window displays the following text:

```
* (c) Jokab Safety AB      *
***** OS ver:1.1.1
Pluto_GW>sys - Load system flash, are you sure? (y/n) y Erase..  OK (1704 ms)
** Ready, please start loading... Load OK
Pluto_GW>cs - system rom CRC = 0xC7E8 Write CRC to flash (y/n)? y
Pluto_GW>boot

*****
PROFIBUS gateway
*****
Serial number: 1002
*****
Software ver : 1.1.2
Software date: 2006-06-13
*****
(c) JOKAB SAFETY AB
*****
ph_gw>
ph_gw> |
```

- The procedure is now finished.