


# Electronic overload relays

EF65



The EF65 is a self-supplied electronic overload relay, which means no extra external supply is needed. They are offering reliable and fast protection for motors in the event of overload or phase failure.

EF65 electronic overload relays are available from 20 A up to 70 A. They are easy to use like thermal overload relays and are compatible with standard motor applications. Electronic overload relays are convincing, above all, due to their wide setting range, high accuracy, high operational temperature range and the option to select a trip class (10E, 20E, 30E). Further features include temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP- and test function and a trip indication. The overload relays can connect directly to AF block contactors. Single mounting kits are available as accessory. The EF65 electronic overload relays have ATEX and IECEx certification.

## Product conformity & compliance

### REACH (Regulation EC 1907/2006)

EF65 and related accessories were classified as articles and, during normal and reasonably foreseeable conditions of use, do not intentionally release any substance or preparation. ABB continuously undertakes communications throughout its supply chain in order to collect information about suppliers' compliance with REACH regulation.

### SVHC (Regulation EC 1907/2006 REACH)

ABB continuously assesses its products for content of Substances of Very High Concern (SVHC), as included in the "Candidate List" by the European Chemicals Agency (ECHA). ABB publishes the data about the products that are having a part with SVHC in the SCIP database.

### RoHS II

EF65 and related accessories are within the scope of directive 2011/65/EU (RoHS II) and amendment 2015/863, starting from July 22 2019.

### WEEE

The Waste Electrical and Electronic Equipment Directive (WEEE Directive) is the European Community directive 2012/19/EU on waste electrical and electronic equipment (WEEE) which, together with the RoHS directive, became European law in February 2003.

**Product sSafety**

Compliance with essential health and safety requirements has been assured by compliance with the applicable product and safety standards. The validation according to the product and safety standards is carried out by third party tests laboratory (STIEE / TL030) in respect of the EN ISO/IEC 17025 European standard, according to IECEE CB scheme. CB certificate has been issued.

**Standards:**

- IEC/EN 60947-1
- IEC/EN 60947-4-1
- IEC/EN 60947-5-1
- IEC/EN 60079-1
- IEC/EN 60079-7
- IEC/EN 60079-14
- IEC/EN 60079-31
- UL 60947-1
- UL 60947-4-1
- UL 60947-5-1


**Directives:**

- EC “Low Voltage Directive” (LVD) 2014/35/EU
- EC “ATEX Directive” 2014/34/EU

**Material declaration**

This section outlines the material composition of EF65-70 as a representative product for the EF65 range. The constituent materials are distributed as follows.

**EF65-70 The total weight of the product is 821 gr.**




Material	% wt
1 Copper	43.0 %
2 PA	25.4 %
3 Stainless steel	15.5 %
4 Steel	11.8 %
5 PCBA	2.6 %
6 Copper alloys	0.5 %
7 Other metal	0.5 %
8 Other thermoplastic	0.4 %
9 PBT	0.3 %
TOTAL	100 %

## Packaging


The tables below provide information for each packaging material used. The card box used for the product material are made of recycled fibers and are 100 % recyclables.

**EF65 packaging material composition: total weight 85 gr.**



Material	% wt
1 Cardbox	95.0 %
2 Paper	5.0 %
TOTAL	100 %

## Product use



### Energy

Power losses for EF65 are indicated in the following table.

Type	Power loss (W/device)
EF65-56	0.85
EF65-70	1.32

## End-of-life

At the end of operating life, constituent components of EF65 electronic overload relays have been optimized in order to reduce waste amount and increase recovery of the material. Metals and polymers contained into EF65 electronic overload relays are characterized by high recycling rates. Most plastic parts are marked for easy sorting.

---

**ABB STOTZ-KONTAKT GmbH**  
Eppelheimer Strasse 82  
69123 Heidelberg, Germany

**[abb.com/lowvoltage](http://abb.com/lowvoltage)**

---

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB AG does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB AG.  
Copyright© 2022 ABB  
All rights reserved