

PRODUCT ENVIRONMENTAL INFORMATION

Time relays

CT-C



ABB time relays provide simple, reliable and economical control solutions in all types of panels. They are typically used in industrial applications and OEM equipment, providing time-delayed switching to start a motor, control a load or manage a process.

The CT-C range combines lower cost with higher value and performance by offering essential functions in a 17.5 mm housing, freeing up room in any control cabinet. The range includes 14 devices, offering both single and multi-functional types, with a time range from 0.05 seconds to 100 hours. Equipped with wide voltage ranges, CT-C time relays allow for use across a huge variety of applications worldwide.

Product conformity & compliance

REACH (Regulation EC 1907/2006)

CT-C time relays and related accessories were classified as articles and, during normal and reasonably foreseeable conditions of use, do not intentionally release any substance or preparation. ABB continuously undertakes communications throughout its supply chain in order to collect information about suppliers' compliance with REACH regulation.

RoHS II

CT-C time relays and related accessories are within the scope of directive 2011/65/EU (RoHS II) and amendment 2015/863, starting from July 22 2019.

SVHC (Regulation EC 1907/2006 REACH)

ABB continuously assesses its products for content of Substances of Very High Concern (SVHC), as included in the "Candidate List" by the European Chemicals Agency (ECHA). ABB publishes the data about the products that are having a part with SVHC in the SCIP database.

WEEE

The Waste Electrical and Electronic Equipment Directive (WEEE Directive) is the European Community directive 2012/19/EU on waste electrical and electronic equipment (WEEE) which, together with the RoHS directive, became European law in February 2003.

Product safety

Compliance with essential health and safety requirements has been assured by compliance with the applicable product and safety standards. The validation according to the product and safety standards is carried out by third party tests laboratory (STIEE / TL030) in respect of the EN ISO/IEC 17025 European standard, according to IECEE CB scheme. CB certificate has been issued.

Standards:

- IEC/EN 61812-1
- UL 508


Directives:

- Low Voltage Directive 2014/35/EU
- EMC directive 2014/30/EU
- RoHS Directive 2011/65/EU incl. 2015/863/EU

Material declaration

This section outlines the material composition of CT-MFC.21 as representative products for CT-C time relays. The constituent materials are distributed as follows.

Time Relay CT-MFC.21. The total weight of the product is 67 gr.




Material		% wt
0	PCBA	44.90%
3	PA	36.80%
8	Copper alloys	11.60%
4	Steel	6.00%
6	PC	0.30%
6	PBT	0.20%
0	Paper	0.20%
	TOTAL	100 %

Packaging

The charts below provide information for each packaging material used. The cardbox and the paper used for the product material are made of recycled fibers and are 100 % recyclables. The polymer films used are marked with the proper identification code and are recyclable.

Time relay CT-MFC.21 packaging material composition: total weight = 13 gr.



Mat	erial:	% wt
0	Cardbox	83.0 %
8	Paper	17.0 %
	TOTAL	100 %

Product use

4

Energy

Power losses are indicated in the following table.

Туре	Power (W) consumption	Apparent (VA) power
Time relay CT-MFC.21	1.0	1.7

End-of-life

At the end of operating life, constituent components of CT-C time relays have been optimized in order to reduce waste amount and increase recovery of the material. Metals and polymers contained into CT-C time relays are characterized by high recycling rates. Most plastic parts are marked for easy sorting.

