MS116- 0.16...0.25A
Motorschutzschalter/ Manual Motor Starter



Vielfaches vom Nennstrom multiples of rated current	Auslösezeit tripping time	
	3 polig three pole	2 polig two pole
3 x Ie	20.6 s	13.5 s
5 x Ie	8.1 s	6.1 s
7.2 x Ie	4.9 s	3.0 s

Auslösekennlinie (aus kaltem Zustand)
Die Ansprechwerte der elektromagnet. Auslöser beziehen sich auf Skala Maximum Ie_{max}
Für Nennströme (3-polig) zwischen dem 3-und 8-fachen des Einstellwertes beträgt die Toleranz der Auslösezeit ±20%
gültig ab Fertigungsdatum KW 34/2014
Tripping characteristic (from cold state)
The values of the electromagn. release refer to scale maximum
For currents (3-pole) between 3 and 8 times the current setting the tolerance of the tripping time is ±20%
valid for production date from week 34/2014

(B)

F102

保密文件，经手人赋有保密义务；未经授权而披露，权利人享有追偿权利

We reserve all rights in this document and in the information contained therein. Reproduction, use or disclosure to third parties without express authority is strictly forbidden. ©Copyright 2014 ABB.

Fuer dieses Dokument und den darin dargestellten Gegenstand behalten wir uns alle Rechte vor. Vervielfaeltigung, Bekanntgabe an Dritte oder Verwertung seines Inhalts sind ohne unsere ausdrückliche Zustimmung verboten. ©Copyright 2014 ABB.

Proprietary and Secret Information

Created by	Frank Hustert		Checked by	Michael Konrad		Approved by	Richard Kommert
Created on	2014-08-01		Checked on	2014-08-13		Approved on	2014-08-13
ECN number	ECN000014041	ECN date	07-10-14	Department	CLD	Scale	%
Revision index	B 1	PRU	DESTO				
Partname	MODEL NAME B.3			Drawing	1SAM200505_F102 B.3		

Title (de)	Auslösekennlinie MS116	Format	Language	Sheet No.	No. Sheets
		A4	DE/EN	18	23
Title (en)	Tripping characteristic	1SAM200505			