Tmax molded case circuit-breakers Tmax XT2



Type of circuit-breaker Frame Poles			XT2 125					
								3,4
			Rated ultimate	short-circuit breaking capacity, Icu		N	S	Н
	(AC) 50-60 Hz 240 V	[kA]	65	100	150	200	200	
	(AC) 50-60 Hz 480 V	[kA]	25	35	65	100	150	
	(AC) 50-60 Hz 600Y/347 V	[kA]	_	-	-	-	-	
	(AC) 50-60 Hz 600 V	[kA]	18	22	25	35	42	
	(DC) 250 V-2 poles in series	[kA]	35	50	65	75	85	
	(DC) 500 V-3 poles in series	[kA]	35	50	65	75	85	
	(DC) 500 V-4 poles in series	[kA]		-	_	_	_	
	(DC) 600 V-3 poles in series	[kA]	_				_	
Trip units:								
The serve are at last in TMF (Fixed treshold)					•			
TMF (Fixed treshold) Thermomagnetic TMA (fully adjustable)					•			
Magnetic only	MA (magnetic only adjustable)				•			
Electronic	Ekip LS/I			••••••	•	•••••	***************************************	
	Ekip I	•		***************************************	•	***************************************	***************************************	
	Ekip LSI			•••••	•	•••••	•••••	
	Ekip LSIG			•••••	•	•	• • • • • • • • • • • • • • • • • • • •	
	Ekip E-LSIG	•		•••••	_	•	• • • • • • • • • • • • • • • • • • • •	
Versions			Fixed, Plug-in, Withdrawable					
Fixing on DIN rail					_			
Operating temperature			-25°C to +70°C					

Compliance with Standards

UL489

CSA C22.2 No. 5

IEC 60947-2


EC Directive:

- "Low voltage directives" (LVD) no. 2006/95/CE
- "Electromagnetic compatibility directive" (EMC) no. 2004/108/CE

Caption

- 1 Insulating plate obligatory
- Overall dimension of optional wiring ducts
- 3 25mm insulating barriers between phases (compulsory) provided
- Front carter obligatory for through door of the panel ≤ 25mm/0,98"





Contact us

Canada

ABB Inc. Low Voltage Products 2117 – 32nd Avenue Lachine, QC, CANADA H8T 3J1

Tel.: 514-420-3100 Fax: 514-420-3137

Toll Free: 1-800-567-0283

LVP.support@ca.abb.com

While all care has been taken to ensure that the information contained in this publication is correct, no responsibility can be accepted for any inaccuracy. The Company reserves the right to alter or modify the information contained herein at any time in the light of technical or other developments. Technical specifications are valid under normal operating conditions only. The Company does not accept any responsibility for any misuse of the product and cannot be held liable for indirect or consequential damages.

©Copyright 2015 ABB Inc. All rights reserved.



