10/29/2020 Abbform



ELECTRIFICATION U.S.

Product life cycle announcement

Open Starters - IEC

In accordance with the ABB global strategy, this product is in the life cycle management process. For process details, please visit Life Cycle Management (https://electrification.us.abb.com/life-cycle-management).

Legacy product line (to be replaced)



Open Starters - IEC

Replacement product line



AF Contactor and MS Components

Affected product list

http://search.abb.com/library/Download.aspx?DocumentID=1SXU100125G0201&LanguageCode=en&DocumentPartId=&Action=Launch+library/Lownload.aspx?DocumentD=1SXU100125G0201&LanguageCode=en&DocumentPartId=&Action=Launch+library/Lownload.aspx?DocumentD=1SXU100125G0201&LanguageCode=en&DocumentPartId=&Action=Launch+library/Lownload.aspx?DocumentD=1SXU100125G0201&LanguageCode=en&DocumentPartId=&Action=Launch+library/Lownload.aspx?DocumentD=1SXU100125G0201&LanguageCode=en&DocumentPartId=&Action=Launch+library/Lownload.aspx?DocumentD=1SXU100125G0201&LanguageCode=en&DocumentPartId=&Action=Launch+library/Lownload.aspx?DocumentD=1SXU100125G0201&LanguageCode=en&DocumentPartId=&Action=Launch+library/Lownload.aspx?DocumentD=1SXU100125G0201&LanguageCode=en&DocumentPartId=&Action=Launch+library/Lownload.aspx?DocumentD=1SXU100125G0201&LanguageCode=en&DocumentPartId=&Action=Launch+library/Lownload.aspx.

Transition benefits

Combination ratings

Electronic coil

Compact

The AF contactor is compact in size and has had its width reduced by up to 30% thanks to an 80% reduction of the coil's energy consumption.

Flexible

AF09...AF370 is perfect for motor starting applications and for solutions where space is limited. Interlocked reversing pairs require no spacing between contactors meaning you can fit more functionality into cabinets or other small enclosures.

Coil terminal access in the front

The AF contactor has its coil terminals accessible from the front. The cables or bars do not have to be disconnected in order to perform voltage measurement or servicing work.

More functionality without adding width

The AF116 ... AF2650 can take up to 2 side mounted auxiliary contact blocks without adding to its width and are delivered with 1 N.O. + 1 N.C. as standard.

https://abb.jpedev.com

10/29/2020 Abbform

LCM phase	Active	Classic	Last time to buy	Limited	Obsolete	
Effective date	Open Starters - IEC	Jan 1, 2020	Jan 15, 2021	Oct 1, 2020	Jan 31, 2021	or

Product returns, pricing and other terms will follow standard ABB U.S. Electrification Life Cycle Management policies summarized below.

LCM phase	Active	Classic	Last time to buy	Limited	Obsolete
status description	Product is fully available for sale, quotation and promotion	Product will be replaced or phased out	Last date purchase orders will be accepted for above current on-hand inventory levels	Purchase orders only accepted for material in-stock	Product is no longer available, pruchase orders not accepted
Product available for sales	Yes	Yes	Yes	Not guaranteed	No
New special pricing agreements (SPAs) and project quotations can be established	Yes	No	No	No	No
New equipment SPAs and project quotations can be established for equipment using these components	Yes	Announced separately	Announced separately	Announced separately	No
SPAs accepted for expansions	Yes	Yes	Yes	No	No
SPA rebate requests accepted per ABB policy	Yes	Yes	Yes	Yes	Yes
Price increases	Announced separately	Announced separately	Announced separately	Announced separately	No
Product stocking levels	Based on product	Based on product	Based on product	Lmited, not being replenished	No
Delivery lead-times	Standard, based on product	Maybe longer than standard	Maybe longer than standard	From stock only, or made to order for quotes previously accepted	No
Product available for new or already quoted projects	Yes	Yes	Yes	Not guaranteed	No
Product available for expansion projects	Yes	Yes	Yes	Not guaranteed*	Please contact Service*
Returns accepted per ABB policy	Based on product	Based on product	Based on product	Based on product	No
Spares available	Yes	Yes	Yes	Not guaranteed*	Please contact Service*
Available in online tools	Yes	Yes	Yes	Not guaranteed*	No

^{*}Please contact ABB Service if there is not a replacement product available in empower.

ABB North America Electrification Services

Available 24/7/365 Phone: 1-888-434-7378 (option 3) email: epis.service@abb.com
website: https://electrification.us.abb.com/services

2/3 https://abb.jpedev.com

10/29/2020 Abbform

Product-specific support resources

Replacement product information

Motor Protection and Control Main Catalog

https://search.abb.com/library/Download.aspx?DocumentID=1SBC100214C0201&LanguageCode=en&DocumentPartId=&Action=Launch

SOC Tool

https://www.lowvoltage-tools.abb.com/soc/Motor

Legacy product information

Open Starters Catalog

https://search.abb.com/library/Download.aspx?DocumentID=1SXU000023C0202& LanguageCode=en&DocumentPartId=CH03-Starters&Action=LaunchAc

Other support information:

- e-Configure (https://econfigure.xe.abb.com/global/)
- Online breaker configurator (https://lowvoltage-configurator.tnb.com/configurator/#/select)
 empower product selector (https://empower.abb.com/ecatalog/ec/EN_NA/c/Electrical_Distribution_1000)
- electrification.us.abb.com (https://electrification.us.abb.com/)
- ABB product news (http://marketlink.tnb.com/)

For additional information, please contact your ABB account manager.

Announcement revision history

	Date	Revision no.	Description
Oct 1, 2020	1		Document creation

ABB Inc. Electrification Business

860 Ridge Lake Blvd. Memphis, TN 38120

electrification.us.abb.com

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction or utilization of its contents - in whole or in parts - is forbidden without prior written consent of ABB Inc. Copyright© 2020 ABB All rights reserved

3/3 https://abb.jpedev.com