

**DISTRIBUTION SOLUTIONS** 

# 38 kV OEM switchgear components

# Medium voltage breaker compartment




ABB is pleased to offer a new 38 kV OEM circuit breaker kit or compartment for the ADVAC® 38 medium voltage vacuum circuit breaker up to 40.5 kV, 40 kA, 3000 A.



### Minimize installation time

 Standard 38 kV, 11-inch phase spacing provides ease of installation



#### Save floor space

- · Space saving compact design
- Two-high stacking compatible



# Reduce shipping time and costs

- 45% lighter weight than competitor products, helping save on shipping time and costs
- Compartment is shipped with the circuit breaker installed



### **Protect assets**

Type tested according to:

- · C37.55-2020
- C37.20.2-2015 Annex C for partial discharge testing
- UL94 V0 flammability primary bushings



# Optimize investment

- Optimized design with compact, single-sized compartment for all 38 kV ratings
- Up to six standard accuracy bushing mounted current transformers per phase



### Reduce maintenance costs

- · Low to no maintenance compartment
- Improved ABB shutter mechanism design
- Rotary wiping TOC contacts

Technical data		
Rated voltage class	kV	38
Tested voltage, Ur	kV	40.5
Continuous current	А	1200, 2000, 3000
System-source short circuit breaking current, Isc	kA	16, 25, 31.5, 40
Lightning impulse withstand voltage, Up drawout	kV	150
Power frequency withstand voltage, Ud	kV	80

Dimensions and weight				
	H	Height	1396.5 mm	54.98 in
		Width	1065 mm	41.93 in
		Depth	1477 mm	58.15 in
(Excluding primary bushings)	WD	Phase distance	280 mm	11 in
		Weight	564 kg	1244 lbs