

CERTIFICATE OF COMPLIANCE

Certificate Number 20180302-E36588
Report Reference E36588-20121214
Issue Date 2018-MARCH-02

Issued to: ABB AB, Control Products
Motorgrand 20
SE-721 61 Vasteras SWEDEN

**This is to certify that
representative samples of** MOTOR CONTROLLERS, MAGNETIC
See Addendum Page for Models.

Have been investigated by UL in accordance with the
Standard(s) indicated on this Certificate.

Standard(s) for Safety: UL 60947-4-1 & CSA C22.2 NO 60947-4-1-14
Low-Voltage Switchgear and Controlgear – Part 4-1:
Contactors and motor-starters – Electromechanical
contactors and motor-starters

Additional Information: See the UL Online Certifications Directory at
www.ul.com/database for additional information

Only those products bearing the UL Certification Mark should be considered as being covered by UL's
Certification and Follow-Up Service.

Look for the UL Certification Mark on the product.



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please
contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>



CERTIFICATE OF COMPLIANCE

Certificate Number 20180302-E36588
Report Reference E36588-20121214
Issue Date 2018-MARCH-02

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements.

Open type, magnetic motor controllers and Type AF265, AF305, AF370, AFS265, AFS305, AFS370, AX260, AX300 or AX370 followed by -30 or -30RT followed by -00, -11, -22, -01, -10, followed by additional suffixes indicating coil voltage. Type AF265N5, or AFS265N5, may be followed by -30, followed by M or R, followed by -00, -11, -22, followed by two additional suffixes. Reversers, open type, AF265, AF305 or AF370, followed by R, followed by -30, followed by -00, -11, -22, followed by additional suffixes indicating coil voltage.

Accessories for AF265, AF305 AF370, AFS265, AFS305, AFS370, AX260, AX300, AX370, AF265N5, AFS265N5R Contactors:

Terminal Shroud Type. LT370-30C, LT300-AL, LT370-AY

Connection Device Type. LL370-30

Connection Bar Type Nos. BEA370/T5, BEA370H/T5, BER370-4, BEP370-30, BEY265-4, BEY370-4, BEY460-4

Terminal Extension Type. LY300, LX370, LW370, LP300

Aux. Contact Blocks Type. CAL19-11, CAL19-11B, CEL19-10, CEL19-01, CAL19X-11

Accessories Type. BFP370-30

Mechanical Interlocks. VM19, VM205/265, VM205/260



Bruce Mahrenholz, Director North American Certification Program
UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

