

Color-Keyed® compression and EZGround® system

One-Hole Lugs

Standard Barrel 600 V to 35 kV

Material: High-Conductivity Wrought Copper
Finish: Electro-Tin Plated

CODE	WIRE SIZE FLEX	BOLT SIZE	DIE CODE	COLOUR CODE
#14-10 AWG	#8 256-30695-1351	1/4	256-30695-1352	N/A
	1/4 256-30695-263	1/4	256-30695-263	N/A
	1/4 54101	1/4	54101	
	#10 54104	1/4	54104	
#8 AWG	23 Navy #8 Weld 37/24 = 14.9 kcmil	5/16	54131	21 RED
	3/8 54132	3/8	54132	
	1/2 256-30695-424	1/2	256-30695-424	
	#12 256-30695-1361	1/2	256-30695-1361	
#6 AWG	#10 54134	5/16	54135	24 BLUE
	3/8 54136	3/8	54136	
	1/2 256-30695-282	1/2	256-30695-282	
	1/2 256-30695-422	1/2	256-30695-422	
#4 AWG	#10 54138	5/16	54139	29 GREY
	3/8 54140	3/8	54140	
	1/2 256-30695-233	1/2	256-30695-233	
	1/2 54147	1/2	54147	
#2 AWG	60 Navy #4 Weld 125/24 = 50.4 kcmil	3/8	54143	33 BROWN
	1/2 54145	1/2	54145	
	1/4 54108	1/4	54108	
	5/16 54147	5/16	54147	
#1 AWG	150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/0223	3/8	54148	37 GREEN
	1/2 54150	1/2	54150	
	1/4 54153	1/4	54153	
	5/16 54153	5/16	54153	
1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/0254	3/8	54109	42 PINK
	1/2 54155	1/2	54155	
	1/2 256-30695-1383	1/2	256-30695-1383	
	1/4 54157	1/4	54157	
2/0 AWG	125 Navy 1/0 Weld 427/0155 133/0282	5/16	54110	45 BLACK
	1/2 54160	1/2	54160	
	1/2 256-30695-131	1/2	256-30695-131	
	5/8 54162	5/8	54162	
3/0 AWG	150 Navy, 2/0 Weld 325/24 = 131 kcmil 133/0316, 259/0227 427/0177	3/8	54111	50 ORANGE
	1/2 54165	1/2	54165	
	1/4 54167	1/4	54167	
	5/16 54168	5/16	54168	
4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/0154	3/8	54112	54 PURPLE
	1/2 54170	1/2	54170	
	1/4 54181	1/4	54181	
	5/8 54182	5/8	54182	
—	550/24 = 222 kcmil 133/0399 259/0286 637/0183	3/8	58163	62 YELLOW
	1/2 58165	1/2	58165	
	1/4 54172	1/4	54172	
	5/16 54173	5/16	54173	
250 kcmil	250 Navy 1/2 54113	3/8	54174	62 YELLOW
	1/2 54113	1/2	54113	
	250 Weld 650/24 = 262 kcmil 259/0311, 703/0189	1/2	58168	66 WHITE
	5/16 54178	5/16	54178	
300 kcmil	300 Navy 1/2 54179	3/8	54179	
	1/2 54114	1/2	54114	66 WHITE
	5/8 54181	5/8	54181	
	300 Weld, 259/0368, 427/0285, 133/0224, 889/0201	1/2	58171	71 RED
350 kcmil	350 Navy 1/2 54115	3/8	54115	71 RED
	5/8 54183	5/8	54183	
	350 Weld, 259/0368, 427/0285, 133/0224, 889/0201	1/2	58174	76 BLUE
	400 Navy 1/2 54116	3/8	54185	76 BLUE
400 kcmil	400 Navy 1/2 54117	3/8	54185	76 BLUE
	400 Weld, 259/0393, 427/0306	1/2	58177	80 N/A
	38 256-30695-338	1/2	54118	87 BROWN
	5/8 54187	5/8	54187	
500 kcmil	500 Navy 1/2 54119	3/8	54120	87 BROWN
	5/8 54189	5/8	54189	
	1100/24 = 444 kcmil 500 Weld, 259/0417 427/0325, 703/0253	5/8	58180	94 GREEN
	1/2 54121	1/2	54121	
600 kcmil	600 Navy 1/2 54122	3/8	54123	99 PINK
	5/8 54190	5/8	54190	
	1325/24 = 535 kcmil 427/0342	1/2	58192	99 PINK
	1/2 54123	1/2	54123	
750 kcmil	750 Navy 1/2 54124	3/8	54125	106 BLACK
	5/8 54191	5/8	54191	
	1000/24 = 400 kcmil 1325/24 = 535 kcmil 427/0342	1/2	58194	99 PINK
	1/2 54124	1/2	54124	
1000 kcmil	1000 Navy 1/2 54125	3/8	54126	125 N/A
	5/8 54192	5/8	54192	
	1325/24 = 535 kcmil 427/0342	1/2	58196	99 PINK
	1/2 54125	1/2	54125	

CODE	WIRE SIZE FLEX	BOLT SIZE	DIE CODE	COLOUR CODE
#14-10 AWG	#8 256-30695-1351	1/4	256-30695-1352	N/A
	1/4 256-30695-263	1/4	256-30695-263	N/A
	1/4 54101	1/4	54101	
	#10 54104	1/4	54104	
#8 AWG	23 Navy #8 Weld 37/24 = 14.9 kcmil	5/16	54131	21 RED
	3/8 54132	3/8	54132	
	1/2 256-30695-424	1/2	256-30695-424	
	#12 256-30695-1361	1/2	256-30695-1361	
#6 AWG	#10 54134	5/16	54135	24 BLUE
	3/8 54136	3/8	54136	
	1/2 256-30695-282	1/2	256-30695-282	
	1/2 256-30695-422	1/2	256-30695-422	
#4 AWG	#10 54138	5/16	54139	29 GREY
	3/8 54140	3/8	54140	
	1/2 256-30695-233	1/2	256-30695-233	
	1/2 54147	1/2	54147	
#2 AWG	60 Navy #4 Weld 125/24 = 50.4 kcmil	3/8	54143	33 BROWN
	1/2 54145	1/2	54145	
	1/4 54108	1/4	54108	
	5/16 54147	5/16	54147	
#1 AWG	150/24 = 60.5 kcmil 175/24 = 70.6 kcmil 133/0223	3/8	54148	37 GREEN
	1/2 54150	1/2	54150	
	1/4 54153	1/4	54153	
	5/16 54153	5/16	54153	
1/0 AWG	100 Navy #1 Weld 225/24 = 90.8 kcmil 133/0254	3/8	54109	42 PINK
	1/2 54155	1/2	54155	
	1/2 256-30695-1383	1/2	256-30695-1383	
	1/4 54157	1/4	54157	
2/0 AWG	125 Navy 1/0 Weld 427/0155 133/0282	5/16	54110	45 BLACK
	1/2 54160	1/2	54160	
	1/2 256-30695-131	1/2	256-30695-131	
	5/8 54162	5/8	54162	
3/0 AWG	150 Navy, 2/0 Weld 325/24 = 131 kcmil 133/0316, 259/0227 427/0177	3/8	54111	50 ORANGE
	1/2 54165	1/2	54165	
	1/4 54167	1/4	54167	
	5/16 54168	5/16	54168	
4/0 AWG	200 Navy 3/0 Weld 450/24 = 182 kcmil 703/0154	3/8	54112	54 PURPLE
	1/2 54170	1/2	54170	
	1/4 54181	1/4	54181	
	5/8 54182	5/8	54182	
—	550/24 = 222 kcmil 133/0399 259/0286 637/0183	3/8	58163	62 YELLOW
	1/2 58165	1/2	58165	
	1/4 54172	1/4	54172	
	5/16 54173	5/16	54173	
250 kcmil	250 Navy 1/2 54113	3/8	54174	62 YELLOW
	1/2 54113	1/2	54113	
	250 Weld 650/24 = 262 kcmil 259/0311, 703/0189	1/2	58168	66 WHITE
	5/16 54178	5/16	54178	
300 kcmil	300 Navy 1/2 54179	3/8	54179	
	1/2 54114	1/2	54114	66 WHITE
	5/8 54181	5/8	54181	
	300 Weld, 259/0368, 427/0285, 133/0224, 889/0201	1/2	58171	71 RED
350 kcmil	350 Navy 1/2 54115	3/8	54115	71 RED
	5/8 54183	5/8	54183	
	350 Weld, 259/0368, 427/0285, 133/0224, 889/0201	1/2	58174	76 BLUE
	400 Navy 1/2 54116	3/8	54185	76 BLUE
400 kcmil	400 Navy 1/2 54117	3/8	54185	76 BLUE
	400 Weld, 259/0393, 427/0306	1/2	58177	80 N/A
	38 256-30695-338	1/2	54118	87 BROWN
	5/8 54187	5/8	54187	
500 kcmil	500 Navy 1/2 54119	3/8	54120	87 BROWN
	5/8 54189	5/8	54189	
	1100/24 = 444 kcmil 500 Weld, 259/0417 427/0325, 703/0253	5/8	58180	94 GREEN
	1/2 54121	1/2	54121	
600 kcmil	600 Navy 1/2 54122	3/8	54123	99 PINK
	5/8 54190	5/8	54190	
	1325/24 = 535 kcmil 427/0342	1/2	58192	99 PINK
	1/2 54123	1/2	54123	
750 kcmil	750 Navy 1/2 54124	3/8	54125	106 BLACK
	5/8 54191	5/8	54191	
	1000/24 = 400 kcmil 1325/24 = 535 kcmil 427/0342	1/2	58194	99 PINK
	1/2 54124	1/2	54124	
1000 kcmil	1000 Navy 1/2 54125	3/8	54126	125 N/A
	5/8 54192	5/8	54192	
	1325/24 = 535 kcmil 427/0342	1/2	58196	99 PINK
	1/2 54125	1/2	54125	

- Narrow-width tongue and barrel, engineered for dimensional consistency the entire length of the lug
- Perfect for connections in limited space applications
- High-conductivity copper alloy construction

**Electro-tin-plated finish
resists corrosion**

- Colour marking system makes connections and verification easy
- Chamfered barrel eases insertion of wire


