

FOOD AND BEVERAGE PRODUCT PORTFOLIO EXPANSION

T&B® Fittings stainless dome drain

Ideal for draining moisture from enclosures and conduit systems.

T&B Fittings



Watch the video



Made of 316 stainless steel for hygiene and corrosion resistance, the NSF certified T&B Fittings stainless dome drain features slotted threads for easy draining and an optional screen to prevent clogging. The drain is UL Type 4X and IP56 listed, making it suitable for use in washdown environments.



All rounded components encourage water run-off to prevent pooling.

Robust 316 stainless steel construction resists corrosion.

Available in 1/2" and 3/4" NPT trade sizes.



Optional screen prevents contaminants from clogging drain.

Slitted threads allow for easy and immediate draining — no waiting until water level exceeds fitting height to drain.

NSF-approved, FDA-compliant integral TPE conduit seal



Installs easily into the bottom of an enclosure, or can be threaded into the end of a low-point conduit body.

ABB Installation Products Inc.
Electrification Business
860 Ridge Lake Blvd.
Memphis, TN 38120

ABB has made every attempt to ensure the accuracy and reliability of the contents of this document. However, all content is provided for general informational purposes only, and ABB makes no guaranty or warranty, express or implied, as to the accuracy of any technical content, or that the information contained in this publication will be error free and all such guarantees or warranties are expressly disclaimed. ABB may change or modify

the contents at any time, without prior notice. We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction or utilization of its contents — in whole or in parts — is forbidden without prior written consent of ABB.
© 2023 ABB Installation Products Inc. and/or its affiliated companies. All rights reserved.