

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Furseweld Exothermic Welding Powder (Main)
Product codes : 15P10, 25P10, 32P10, 45P10, 65P10, 90P10, 115P10, 150P10, 200P10 & 250P10.

1.2. Relevant identified uses of the substance or mixture and uses advised against

1.2.1. Relevant identified uses

Main use category : Industrial use
Use of the substance/mixture : Copper Based Welding Powder with Aluminium

1.2.2. Uses advised against

No additional information available

1.3. Details of the supplier of the safety data sheet

Manufacturer

ABB Furse
Wilford Road, Nottingham
United Kingdom
NG2 1EB

Tel: +44 (0) 115 964 3700 Fax: +44 (0) 115 986 0071
www.furse.com

1.4. Emergency telephone number

Emergency number : Tel: +44 (0) 115 964 3700

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification according to Regulation (EC) No. 1272/2008 [CLP]

Water-react. 2	H261
Acute Tox. 4 (Oral)	H302
Acute Tox. 4 (Inhalation:dust,mist)	H332
Eye Dam. 1	H318
Aquatic Acute 1	H400
Aquatic Chronic 1	H410

Full text of hazard classes, H- and EUH-statements: see section 16

Adverse physicochemical, human health and environmental effects

No additional information available

2.2. Label elements

Labelling according to Regulation (EC) No. 1272/2008 [CLP]

Hazard pictograms (CLP) :



GHS02

GHS05

GHS07

GHS09

Signal word (CLP) :

Danger

Contains

Copper(I) oxide

Furseweld™ Exothermic Welding Powder (Main)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Hazard statements (CLP)	: H261 - In contact with water releases flammable gases. H302+H332 - Harmful if swallowed or if inhaled. H318 - Causes serious eye damage. H410 - Very toxic to aquatic life with long lasting effects.
Precautionary statements (CLP)	: P231+P232 - Handle and store contents under inert gas. Protect from moisture. P273 - Avoid release to the environment. P280 - Wear protective gloves/protective clothing/eye protection/face protection/hearing protection. P302+P335+P334 - IF ON SKIN: Brush off loose particles from skin. Immerse in cool water or wrap in wet bandages. P305+P351+P338+P310 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor. P370+P378 - In case of fire: Use media other than water to extinguish. P391: Collect spillage.
Unknown acute toxicity (CLP) - SDS	: 24% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral) 14% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal) 85% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))
Unknown hazards to the aquatic environment (CLP)	: Contains 5 % of components with unknown hazards to the aquatic environment

2.3. Other hazards

This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII

This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII

The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

Frequent inhalation of dust over a long period increases the risk of developing lung diseases. Copper oxide may by repeated or prolonged inhalation occasionally cause ulceration and perforation of the nasal septum. Long term exposure to copper containing dusts may cause allergic dermatitis.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Copper(I) oxide	CAS-No.: 1317-39-1 EC-No.: 215-270-7 EC Index-No.: 029-002-00-X	< 80	Acute Tox. 4 (Oral), H302 (ATE=470 mg/kg bodyweight) Acute Tox. 4 (Inhalation), H332 (ATE=3.69 mg/l/4h) Eye Dam. 1, H318 Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)
Copper oxide (CuO)	CAS-No.: 1317-38-0 EC-No.: 215-269-1 EC Index-No.: 029-016-00-6 REACH-no: 01-2119502447-44	< 80	Aquatic Acute 1, H400 (M=100) Aquatic Chronic 1, H410 (M=10)
Copper substance with national workplace exposure limit(s) (IE)	CAS-No.: 7440-50-8 EC-No.: 231-159-6 EC Index-No.: 029-024-00-X	< 20	Not classified.
Aluminum substance with national workplace exposure limit(s) (IE) (Note T)	CAS-No.: 7429-90-5 EC-No.: 231-072-3 EC Index-No.: 013-002-00-1	< 10	Not classified.

Furseweld™ Exothermic Welding Powder (Main)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Name	Product identifier	%	Classification according to Regulation (EC) No. 1272/2008 [CLP]
Calcium silicon*	CAS-No.: 12013-56-8 EC-No.: 234-588-7	< 5	Water-react. 2, H261

Note T : This substance may be marketed in a form which does not have the physical hazards as indicated by the classification in the entry in Part 3. If the results of the relevant method or methods in accordance with Part 2 of Annex I of this Regulation show that the specific form of substance marketed does not exhibit this physical property or these physical hazards, the substance shall be classified in accordance with the result or results of this test or these tests. Relevant information, including reference to the relevant test method(s) shall be included in the safety data sheet.

*This substance does not contribute to any health hazards indicated in section 2 of this document.

Full text of H- and EUH-statements: see section 16

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a POISON CENTER/doctor if you feel unwell.
First-aid measures after skin contact	: Brush off loose particles from skin. Immerse in cool water/wrap in wet bandages. Obtain medical attention if irritation persists.
First-aid measures after eye contact	: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER/doctor.
First-aid measures after ingestion	: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person. Call a POISON CENTER/doctor if you feel unwell.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/effects after inhalation	: Harmful if inhaled. May cause irritation to the respiratory tract. Inhalation of fumes may cause metal fume fever.
Symptoms/effects after skin contact	: May cause skin irritation. Repeated exposure may cause skin dryness or cracking. Risk of thermal burns on contact with molten product.
Symptoms/effects after eye contact	: Causes serious eye damage. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. May cause burns. Risk of thermal burns on contact with molten product.
Symptoms/effects after ingestion	: Harmful if swallowed. May cause gastrointestinal irritation, nausea, vomiting and diarrhea.

4.3. Indication of any immediate medical attention and special treatment needed

Symptoms may be delayed. In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible).

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: Sand.
Unsuitable extinguishing media	: Do not use water. Do not use hand-held extinguishers.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Products of combustion may include, and are not limited to: oxides of carbon. Metallic oxides. If ignition temperatures exceed 454°C/850°F for the starting weld metal and 954°C/1750°F for the main weld metal, the material may be accidentally ignited. In this case, large amounts of water should hinder and then control the spread of fire. The ignition of large amounts of weld metal could possibly result in varying volumes of smoke.
-------------	---

5.3. Advice for firefighters

Protection during firefighting	: Keep upwind of fire. Wear full fire fighting turn-out gear (full Bunker gear) and respiratory protection (SCBA).
--------------------------------	--

Furseweld™ Exothermic Welding Powder (Main)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Use personal protection recommended in Section 8. Isolate the hazard area and deny entry to unnecessary and unprotected personnel.

6.1.1. For non-emergency personnel

No additional information available

6.1.2. For emergency responders

No additional information available

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if product enters sewers or public waters. Avoid release to the environment. Collect spillage.

6.3. Methods and material for containment and cleaning up

For containment : Remove ignition sources. Contain spill, then place in a suitable container. Minimize dust generation. Do not flush to sewer or allow to enter waterways. Use appropriate Personal Protective Equipment (PPE).

Methods for cleaning up : Sweep or shovel spills into appropriate container for disposal. All spilled or leaked materials should be swept up by soft natural fibre brushes. Use non-sparking or plastic scoops to pick up the material. Provide ventilation.

6.4. Reference to other sections

For further information refer to section 8: "Exposure controls/personal protection".

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : Do not allow contact with water.
Precautions for safe handling : Avoid contact with skin and eyes. Avoid breathing dust/fume/gas/mist/vapours/spray. Do not swallow. Handle and open container with care. When using do not eat, drink or smoke. Use only outdoors or in a well-ventilated area. Handle under inert gas.
Hygiene measures : Wash contaminated clothing before reuse. Wash hands, forearms and face thoroughly after handling.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Keep out of the reach of children. Keep container tightly closed. Store in a well-ventilated place. Store in a dry place. Protect from moisture. Protect containers from physical damage.
Maximum storage period : 2 year
Special rules on packaging : Store in a closed container.

7.3. Specific end use(s)

Copper Based Welding Powder with Aluminium.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

8.1.1. National occupational exposure and biological limit values

Aluminum (7429-90-5)

Ireland - Occupational Exposure Limits

OEL TWA [1]	1 mg/m ³ (respirable fraction)
-------------	---

Furseweld™ Exothermic Welding Powder (Main)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aluminum (7429-90-5)	
OEL STEL	3 mg/m ³ (calculated-respirable dust)
Copper (7440-50-8)	
Ireland - Occupational Exposure Limits	
OEL TWA [1]	0.2 mg/m ³ (fume) 1 mg/m ³ (dusts and mists)
OEL STEL	2 mg/m ³ (dusts and mists) 0.6 mg/m ³ (calculated-fume)

8.1.2. Recommended monitoring procedures

Monitoring methods	
Monitoring methods	Consult the relevant monitoring standards for the region.

8.1.3. Air contaminants formed

No additional information available

8.1.4. DNEL and PNEC

Additional information : Not applicable

8.1.5. Control banding

No additional information available

8.2. Exposure controls

8.2.1. Appropriate engineering controls

Appropriate engineering controls:

Ensure good ventilation of the work station. Provide readily accessible eye wash stations and safety showers.

8.2.2. Personal protection equipment

Personal protective equipment:

Equipment must be suitable for welding purposes.

8.2.2.1. Eye and face protection

Eye protection:

Safety eyewear complying with an approved standard such as the European Standard EN166 should be used when a risk assessment indicates this is necessary to avoid exposure to liquid splashes, mists or dusts.

8.2.2.2. Skin protection

Skin and body protection:

Wear suitable protective clothing

Hand protection:

Chemical resistant gloves (according to European standard NF EN 374 or equivalent)

8.2.2.3. Respiratory protection

Respiratory protection:

In case of insufficient ventilation, wear suitable respiratory equipment. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator.

8.2.2.4. Thermal hazards

Thermal hazard protection:

Use personal protective equipment as required.

8.2.3. Environmental exposure controls

Environmental exposure controls:

Avoid release to the environment.

Furseweld™ Exothermic Welding Powder (Main)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Other information:

Handle in accordance with good industrial hygiene and safety procedures. Do not eat, drink or smoke when using this product.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Solid (granular)
Colour	: Black. Grey.
Odour	: Odourless.
Odour threshold	: Not available
Melting point	: 1095 °C
Freezing point	: Not available
Boiling point	: Not applicable
Flammability	: In contact with water releases flammable gases. Not flammable according UN Test N.1
Explosive properties	: Not applicable.
Explosive limits	: Not applicable
Lower explosion limit	: Not applicable
Upper explosion limit	: Not applicable
Flash point	: Not applicable
Auto-ignition temperature	: > 955 °C
Decomposition temperature	: Not available
pH	: Not available
pH solution	: Not available
Viscosity, kinematic	: Not applicable
Solubility	: Insoluble in water.
Partition coefficient n-octanol/water (Log Kow)	: Not available
Vapour pressure	: Not applicable
Vapour pressure at 50 °C	: Not available
Density	: Not available
Relative density	: ≈ 6
Relative vapour density at 20 °C	: Not applicable
Particle size	: Not available
Particle size distribution	: Not available
Particle shape	: Not available
Particle aspect ratio	: Not available
Particle aggregation state	: Not available
Particle agglomeration state	: Not available
Particle specific surface area	: Not available
Particle dustiness	: Not available

9.2. Other information

9.2.1. Information with regard to physical hazard classes

No additional information available

9.2.2. Other safety characteristics

Relative evaporation rate (butylacetate=1) : Not applicable

SECTION 10: Stability and reactivity

10.1. Reactivity

No dangerous reactions known under normal conditions of use.

10.2. Chemical stability

Stable under normal conditions.

Furseweld™ Exothermic Welding Powder (Main)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

10.3. Possibility of hazardous reactions

In contact with water releases flammable gases. No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Heat. Dust formation. Incompatible materials.

10.5. Incompatible materials

Moisture.

10.6. Hazardous decomposition products

May include, and are not limited to: oxides of carbon. Metallic oxides.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Acute toxicity (oral) : Harmful if swallowed.
Acute toxicity (dermal) : Not classified.
Acute toxicity (inhalation) : Harmful if inhaled.

Furseweld™ Alumina-Thermic Welding Powder

ATE CLP (oral)	470 mg/kg bodyweight
ATE CLP (dust,mist)	3.69 mg/l/4h

Copper(I) oxide (1317-39-1)

LD50 oral rat	470 mg/kg
LD50 dermal rat	> 2000 mg/kg
LC50 inhalation rat	3.69 mg/l/4h

Copper oxide (CuO) (1317-38-0)

LD50 oral rat	> 2500 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 423 (Acute Oral toxicity - Acute Toxic Class Method)
LD50 dermal rat	> 2000 mg/kg

Aluminum (7429-90-5)

LD50 oral rat	> 15900 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 401 (Acute Oral Toxicity)
LC50 inhalation rat	> 0.888 mg/l air Animal: rat, Animal sex: male, Guideline: OECD Guideline 403 (Acute Inhalation Toxicity)

Copper (7440-50-8)

LD50 dermal rat	> 2000 mg/kg bodyweight Animal: rat, Guideline: OECD Guideline 402 (Acute Dermal Toxicity), Guideline: EU Method B.3 (Acute Toxicity (Dermal)), Guideline: EPA OTS 798.1100 (Acute Dermal Toxicity), Guideline: other:
LC50 inhalation rat	> 5.11 mg/l/4h

Unknown acute toxicity (CLP) - SDS : 24% of the mixture consists of ingredient(s) of unknown acute toxicity (Oral)
14% of the mixture consists of ingredient(s) of unknown acute toxicity (Dermal)
85% of the mixture consists of ingredient(s) of unknown acute toxicity (Inhalation (Dust/Mist))

Skin corrosion/irritation : Not classified.
Additional information : Based on available data, the classification criteria are not met.
Serious eye damage/irritation : Causes serious eye damage.
Respiratory or skin sensitisation : Not classified.
Additional information : Based on available data, the classification criteria are not met.

Furseweld™ Exothermic Welding Powder (Main)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Germ cell mutagenicity	: Not classified.
Additional information	: Based on available data, the classification criteria are not met.
Carcinogenicity	: Not classified.
Additional information	: Based on available data, the classification criteria are not met.
Reproductive toxicity	: Not classified.
Additional information	: Based on available data, the classification criteria are not met.

Aluminum (7429-90-5)

NOAEL (animal/male, F0/P)	1000 mg/kg bodyweight Animal: rat, Animal sex: male, Guideline: OECD Guideline 422 (Combined Repeated Dose Toxicity Study with the Reproduction / Developmental Toxicity Screening Test)
---------------------------	--

STOT-single exposure	: Not classified.
Additional information	: Based on available data, the classification criteria are not met.
STOT-repeated exposure	: Not classified.
Additional information	: Based on available data, the classification criteria are not met.

Aluminum (7429-90-5)

LOAEC (inhalation, rat,dust/mist/fume, 90 days)	0.05 mg/l air Animal: rat, Guideline: OECD Guideline 413 (Subchronic Inhalation Toxicity: 90-Day Study)
---	---

Aspiration hazard	: Not classified.
Additional information	: Based on available data, the classification criteria are not met.

Furseweld™ Alumina-Thermic Welding Powder

Viscosity, kinematic	Not applicable
----------------------	----------------

11.2. Information on other hazards

11.2.1. Endocrine disrupting properties

Endocrine disrupting properties	: The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %
---------------------------------	--

11.2.2. Other information

Other information	: Likely routes of exposure: ingestion, inhalation, skin and eye
-------------------	--

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: Very toxic to aquatic life with long lasting effects.
Unknown hazards to the aquatic environment (CLP)	: Contains 5 % of components with unknown hazards to the aquatic environment
Hazardous to the aquatic environment, short-term (acute)	: Very toxic to aquatic life.
Hazardous to the aquatic environment, long-term (chronic)	: Very toxic to aquatic life with long lasting effects.

Copper(I) oxide (1317-39-1)

EC50 - Crustacea [1]	0.51 mg/l (Exposure time: 48 h - Species: Daphnia magna)
EC50 96h - Algae [1]	65 mg/l (Species: Desmodesmus subspicatus)
EC50 96h - Algae [2]	0.021 – 0.037 mg/l (Species: Pseudokirchneriella subcapitata)
EC50 96h algae (3)	0.055 – 0.076 mg/l (Species: Pseudokirchneriella subcapitata [static])

Aluminum (7429-90-5)

EC50 72h - Algae [1]	1.05 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
----------------------	---

Furseweld™ Exothermic Welding Powder (Main)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Aluminum (7429-90-5)	
EC50 72h - Algae [2]	0.2 mg/l Test organisms (species): Pseudokirchneriella subcapitata (previous names: Raphidocelis subcapitata, Selenastrum capricornutum)
Copper (7440-50-8)	
LC50 - Fish [1]	0.0068 – 0.0156 mg/l (Exposure time: 96 h - Species: Pimephales promelas)
LC50 - Fish [2]	< 0.3 mg/l (Exposure time: 96 h - Species: Pimephales promelas [static])
EC50 - Crustacea [1]	0.03 mg/l (Exposure time: 48 h - Species: Daphnia magna [Static])
EC50 72h - Algae [1]	0.0426 – 0.0535 mg/l (Species: Pseudokirchneriella subcapitata [static])
EC50 96h - Algae [1]	0.031 – 0.054 mg/l (Species: Pseudokirchneriella subcapitata [static])

12.2. Persistence and degradability

Furseweld™ Alumina-Thermic Welding Powder	
Persistence and degradability	The product solely consists of inorganic compounds, which are not biodegradable. Insufficient data on biodegradability and mobility of composition.

12.3. Bioaccumulative potential

Furseweld™ Alumina-Thermic Welding Powder	
Bioaccumulative potential	Not established.
Copper(I) oxide (1317-39-1)	
BCF - Fish [1]	(does not generally accumulate)

12.4. Mobility in soil

No additional information available

12.5. Results of PBT and vPvB assessment

PBT : No
vPvB : No

Furseweld™ Alumina-Thermic Welding Powder	
This substance/mixture does not meet the PBT criteria of REACH regulation, annex XIII	
This substance/mixture does not meet the vPvB criteria of REACH regulation, annex XIII	

12.6. Endocrine disrupting properties

Endocrine disrupting properties : The mixture does not contain substance(s) included in the list established in accordance with Article 59(1) of REACH for having endocrine disrupting properties, or is not identified as having endocrine disrupting properties in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2018/605 at a concentration equal to or greater than 0,1 %

12.7. Other adverse effects

Additional information : No other effects known

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Product/Packaging disposal recommendations : Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation.

Furseweld™ Exothermic Welding Powder (Main)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

SECTION 14: Transport information

In accordance with ADR

14.1. UN number or ID number

UN-No. (ADR) : UN 2813

14.2. UN proper shipping name


Proper Shipping Name (ADR) : WATER-REACTIVE SOLID, N.O.S. (Limited quantity)

14.3. Transport hazard class(es)

ADR

Transport hazard class(es) (ADR) : 4.3

Danger labels (ADR) : 4.3



14.4. Packing group

Packing group (ADR) : II

14.5. Environmental hazards

Dangerous for the environment : Yes

Other information : No supplementary information available.

14.6. Special precautions for user

Special transport precautions : Do not handle until all safety precautions have been read and understood.

Overland transport

Limited quantities (ADR) : 500g. The product as packaged does not exceed this limited quantity.

Orange plates :



14.7. Maritime transport in bulk according to IMO instruments

Not applicable

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.1.1. EU-Regulations

Contains no REACH substances with Annex XVII restrictions

Contains no REACH candidate substance.

Contains no REACH Annex XIV substances

Contains no substance subject to Regulation (EU) No 649/2012 of the European Parliament and of the Council of 4 July 2012 concerning the export and import of hazardous chemicals.

Contains no substance subject to Regulation (EU) No 2019/1021 of the European Parliament and of the Council of 20 June 2019 on persistent organic pollutants

15.1.2. National regulations

Ireland

Irish National Regulations : Not determined.

Furseweld™ Exothermic Welding Powder (Main)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

15.2. Chemical safety assessment

No chemical safety assessment has been carried out

SECTION 16: Other information

Abbreviations and acronyms

°C – Degrees Celsius
°F – Degrees Fahrenheit
ADR – European Agreement concerning the International Carriage of Dangerous Goods by Road.
ACGIH – American Conference of Governmental Industrial Hygienists
ATE – Acute Toxicity Estimate
BCF – Bioconcentration Factor
BEI – Biological Exposure Index
CAS – Chemical Abstracts Service
CLP – Regulation (EC) No 1272/2008 on the Classification, Labeling and Packaging of substances and mixtures.
CMR – Carcinogen, Mutagen, Reproductive toxin
cP – centipoise (unit of dynamic viscosity)
cSt – centistokes (unit of kinematic viscosity)
DNEL – Derived No-effect Level
DMEL – Derived Minimal Effect Level
EC50 – Half maximal effective concentration
ECHA – European Chemicals Agency
EC-No. – European Community number
EU – European Union
GHS – Globally Harmonized System of Classification and Labelling of Chemicals
h – Hours
IATA – International Air Transport Association
IC50 – Inhibition concentration
IDLH – Immediately Dangerous to Life or Health
IMDG – International Maritime Dangerous Goods
IOELV – Indicative Occupational Exposure Limit Value
KIFS – Swedish Chemicals Agency's (KemI's) Code of Statutes
kPa – kilopascal
Koc – Adsorption Coefficient
Kow – Octanol-Water Partition Coefficient
LC50 – Median Lethal Concentration
LD50 – Median Lethal Dose
LOAEL – Lowest Observed Adverse Effect level
mg/l – Milligram per liter
mg/kg – Milligram per kilogram
mg/m³ – Milligram per cubic meter
Min – Minutes
NIOSH – National Institute for Occupational Safety and Health
NOEC – No Observed Effect Concentration
NO(A)EL – No Observed (Adverse) Effect Level
N.O.S. – Not Otherwise Specified
OEL – Occupational Exposure Limit
PBT - Persistent, Bioaccumulative and Toxic
PCN – Poison Centre Notification
PNEC – Predicted No Effect Concentration
ppm – Parts per million
PVC – Polyvinyl chloride
REACH - Registration, Evaluation, Authorisation and Restriction of Chemicals Regulation (EC) No 1907/2006
RID – European Agreement concerning the International Carriage of Dangerous Goods by Rail
SDS – Safety Data Sheet
STEL – Short Term Exposure Limit
STOT – Specific Target Organ Toxicity
SVHC – Substance of Very High Concern (CMR, vPvB, PBT)
TDI – Tolerable Daily Intake

Furseweld™ Exothermic Welding Powder (Main)

Safety Data Sheet

according to the REACH Regulation (EC) 1907/2006 amended by Regulation (EU) 2020/878

Abbreviations and acronyms

TLV – Threshold Limit Value
TWA – Time Weighted Average
UFI – Unique Formulation Identifier
UN – United Nations
vPvB - Very Persistent and Very Bioaccumulative
WEL – Workplace Exposure Limit
WGK – Wassergefährdungsklasse – German water quality classification

Data sources : REGULATION (EC) No 1272/2008 OF THE EUROPEAN PARLIAMENT AND OF THE COUNCIL of 16 December 2008 on classification, labelling and packaging of substances and mixtures, amending and repealing Directives 67/548/EEC and 1999/45/EC, and amending Regulation (EC) No 1907/2006.

Other information : None.
Prepared by : Nexreg Compliance Inc.
www.Nexreg.com



Full text of H- and EUH-statements

Acute Tox. 4 (Inhalation)	Acute toxicity (inhal.), Category 4
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Aquatic Acute 1	Hazardous to the aquatic environment — Acute Hazard, Category 1
Aquatic Chronic 1	Hazardous to the aquatic environment — Chronic Hazard, Category 1
Eye Dam. 1	Serious eye damage/eye irritation, Category 1
H261	In contact with water releases flammable gases.
H302	Harmful if swallowed.
H318	Causes serious eye damage.
H332	Harmful if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
Water-react. 2	Substances and Mixtures which, in contact with water, emit flammable gases, Category 2

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]

Water-react. 2	H261	Calculation method
Acute Tox. 4 (Oral)	H302	Calculation method
Acute Tox. 4 (Inhalation:dust,mist)	H332	Calculation method
Eye Dam. 1	H318	Calculation method
Aquatic Acute 1	H400	Calculation method
Aquatic Chronic 1	H410	Calculation method

Safety Data Sheet (SDS), EU - Nexreg Annex II 2021

Disclaimer: We believe the statements, technical information and recommendations contained herein are reliable, but they are given without warranty or guarantee of any kind. The information contained in this document applies to this specific material as supplied. It may not be valid for this material if it is used in combination with any other materials. It is the user's responsibility to satisfy oneself as to the suitability and completeness of this information for the user's own particular use.