

TECHNICAL DATA SHEET

PMAJACK - MREIR - Metal Fitting

Female thread terminations for braided hose





CE CH

Applications:

• In combination with PMAJACK braided hoses

Features & Benefits:

- Very high impact resistance
- Suitable for round multi-pin connectors
- Offers excellent termination for braids
- Can be manufactured also in small quantities
- · Different thread types and sizes are available on request

Materials:

- Fitting body: black anodised aluminium
- Clamping ring: made from specially modified polyamide 6

Compatible with:

• PMAJACK braids

Colour:

• Black

Chemical properties:


 Please refer to www.pma.ch (Technical Information / Chemical Resistance)

Environmental properties:

- Free from halogens and cadmium
- RoHS and REACH compliant

Product selection:											
Part no.	Thread size	Fits to I	PMAJACK bra	id (NW):		Dimens	ions in mn	n (nom.)		Weight	Packing unit
black	UN	F.66	C.66	L.66	g	L	d1	d2	d3	kg/100 pcs	pcs/PU
MREIR-U3529	17/16" - 18	25 - 40	30 & 40	25 - 40	9.0	37.5	30.0	40.0	40.5	2.8	20

 $Our \ customer \ service \ dept. \ or \ local \ distribution \ partner \ will \ be \ pleased \ to \ help \ you \ concerning \ product \ availability \ and \ lead \ time$



Mechanical Properties:	Value: Test parameters:	Test method:
Tensile modulus	1'200 3'700 N/mm²	ISO 527
Tensile strength	45 65 N/mm²	ISO 527
Notched bar impact test	4 20 kJ/m²	ISO 180/1C

Thermal properties:	Value:	Test parameters:	Test method:
Continuous application temperature	– 40 + 105°C		PMA DO 9.21-4510
Upper application temperature	+ 120°C	(20'000 h)	PMA DO 9.21-4360
Short-term	+ 160°C	(168 h)	PMA DO 9.21-4360

Content of delivery:

• Female thread adapter with clamping ring

