

TECHNICAL DATA SHEET

PMA Accessories - S-HT - Cable clipSelf Adhesive Cable Clip

PMA



CE CK

Applications:

· For guiding and fixation of cabels

Features & Benefits:

- Self-extinguishing UL94/V2
- Quickly and easy installation
- Safe snap lock
- Rounded edges to protect the cables
- Static transversal strength + 22°C = 1.000 g, (0250S base 5.5 cm2)

Materials:

• High-grade, specially formulated polyamide 6

Colour:

Light grey

Chemical properties:

Please refer to www.pma.ch
(Technical Information / Chemical Resistance)

Optional:


- · Permanent adhevise with adhevise strength
- · Adhesive: acrylate
- Adhesive carrier: polyurethane cellular materials
- Adhesive tape thickness: 0.8 mm
- Protection cover: silicone-threated paper

Environmental properties:

- Free from halogens and cadmium
- RoHS and REACH compliant

Product selection:										
Part no.	Dimensions in mm (nom.)						Static loading capacity	Weight	Packing unit	
light grey	А	В	С	D	E	max. cable diameter	kg	kg/100 pcs	pcs/PU	
0188S-HT	19.3	16.0	9.0	2.6	10.0	5.2	0.3	0.1	100	
0250S-HT	25.3	21.7	10.5	2.9	16.0	6.2	0.5	0.2	100	
0375S-HT	25.3	25.2	13.5	3.2	16.0	9.0	0.6	0.3	100	
0500S-HT	25.3	30.6	18.2	3.4	16.0	13.0	0.7	0.4	100	
0625S-HT	30.3	34.4	20.7	3.5	18.0	16.0	1.0	0.5	100	
0750S-HT	30.1	37.5	25.5	3.6	17.0	20.0	1.1	0.6	50	
1000S-HT	50.5	56.4	35.0	4.3	32.0	28.0	2.5	1.8	50	

Our customer service dept. or local distribution partner will be pleased to help you concerning product availability and lead time



Thermal properties:	Value:	Test parameters:	Test method:
Continuous application temperature	−50 +105°C		PMA DO 9.21-4510
Upper application temperature	+120°C	(20'000 h)	PMA DO 9.21-4360
Short-term	+160°C	(168 h)	PMA DO 9.21-4360

