

TECHNICAL DATA SHEET

PMA Accessories - MR-M/M - Thread reducer

Metal metric thread

PMA



CE CH

Features & Benefits:

• Reduction of threaded or clearance holes to smaller thread sizes

Materials:

• Nickel-plated brass

Compatible with:

• PMAFIX Pro, PMAFIX, PMA Smart Line fittings

Temperature range:

• -60°C ... +200°C

Conforms to:

• Both threads according to EN 60423

Environmental properties:

- Free from halogens and cadmium
- RoHS and REACH compliant

| Product selection: | | | | | | | |
|--------------------|---------------------|--------------------|-------------------------|------|------|------------|--------------|
| Part no. | Thread size | | Dimensions in mm (nom.) | | | Weight | Packing unit |
| | metric (outside) | metric (inside) | g | L | d2 | kg/100 pcs | pcs/PU |
| M16M12M | M16 x 1.5 | M12 x 1.5 | 6.0 | 8.5 | 20.0 | 0.7 | 100 |
| M20M12M | M20 x 1.5 | M12 x 1.5 | 6.5 | 9.0 | 24.0 | 1.6 | 100 |
| M20M16M | M20 x 1.5 | M16 x 1.5 | 6.5 | 9.0 | 24.0 | 1.0 | 100 |
| M25M16M | M25 x 1.5 | M16 x 1.5 | 7.0 | 10.0 | 30.0 | 2.7 | 100 |
| M25M20M | M25 x 1.5 | M20 x 1.5 | 7.0 | 10.0 | 30.0 | 1.8 | 100 |
| M32M20M | M32 x 1.5 | M20 x 1.5 | 8.0 | 11.5 | 39.0 | 5.6 | 50 |
| M32M25M | M32 x 1.5 | M25 x 1.5 | 8.0 | 11.5 | 39.0 | 3.8 | 50 |
| M40M25M | M40 x 1.5 | M25 x 1.5 | 9.0 | 12.5 | 50.0 | 9.6 | 50 |
| M40M32M | M40 x 1.5 | M32 x 1.5 | 9.0 | 12.5 | 50.0 | 6.2 | 50 |
| M50M32M | M50 x 1.5 | M32 x 1.5 | 10.0 | 14.0 | 57.0 | 15.1 | 25 |
| M50M40M | M50 x 1.5 | M40 x 1.5 | 10.0 | 14.0 | 57.0 | 9.5 | 25 |
| M63M40M | M63 x 1.5 | M40 x 1.5 | 10.0 | 14.0 | 70.0 | 21.7 | 10 |
| M63M50M | M63 x 1.5 | M50 x 1.5 | 10.0 | 14.0 | 70.0 | 15.4 | 10 |

Our customer service dept. or local distribution partner will be pleased to help you concerning product availability and lead time



