

TECHNICAL DATA SHEET

# **PMA Divisible System - SGB - Tube clamp** Steel, galvanized

# PMA



C€ FR

## **Applications:**

• In wide range of applications in all industries

## Features & Benefits:

- For the mounting of static conduits
- Elastomer profile, free from halogens
- Smooth connection to PMAFLEX corrugated conduits
- Good resistance to ozone and ageing

#### Materials:

- Clamp: galvanized steel (stainless steel available on request)
- Profile: elastomer (EPDM)

#### Compatible with:

• PMA Divisible System Conduits

# Conforms to:

• DIN 3016

### **Chemical properties:**


Resistant to alcohols, acids and alkalies
Please refer to www.pma.ch
(Technical Information / Chemical Resistance)

## **Environmental properties:**

- Free from halogens and cadmium
- RoHS and REACH compliant

Product selection:									
Part no.	Conduit size	Dimensions in mm (nom.)					Weight	Packing unit	
	NW	d1	A	В	С	М	kg/100 pcs	pcs/PU	
SGB-14	14	17.0	34.0	13.0	14.2	M4	0.5	100	
SGB-14-6.4	14	17.0	35.1	19.0	19.7	М6	1.5	100	
SGB-20	20	24.0	40.9	15.0	20.0	M5	1.1	50	
SGB-23	26	30.0	46.5	15.0	23.0	M5	1.3	30	

Our customer service dept. or local distribution partner will be pleased to help you concerning product availability and lead time



Thermal properties:	Value:	Test parameters:	Test method:
Continuous application temperature	−50 +105°C		PMA DO 9.21-4510
Upper application temperature	+120°C	(20'000 h)	PMA DO 9.21-4360
Short-term	+160°C	(168 h)	PMA DO 9.21-4360

# Content of delivery:

• Tube clamp

