Item	Qty.	Description	Price per unit	Amount	Ì

Manual Call Point, red, EN 54, part	Carry:				
The Manual Call Point HFM/A 1.1 is alarm detector zone.					
The triggering method corresponds to The Manual Call Point latches.	The triggering method corresponds to "type B – indirect triggering" to EN 54-11.				
A visual display indicates the Manua The Manual Call Point can be used a Both SM and FM cable entries are a					
Operating voltage	10 – 30 V DC				
Dimensions (W x H x D) Connection	(supplied by the zone) 126 x 126 x 35 mm Screw terminals				
Cable entry point	Max. 1.5 mm²				
Top and bottom Rear wall	2 pcs. M20 x 1.5 mm 2 pcs. 24 x 10 mm 420 g				
Weight Degree of protection Rel. humidity	420 g IP43 5 – 95%				
Ambient temperature	(non-condensing) -20 to +60 °C (continuous operation, without icing)				
Manual Call Point	-25 to +70 °C (max. 12 hours) To EN54-11, type B				
CPR number:	0786-CPR-21702				
Manufacturer:	ABB STOTZ-KONTAKT				
Type:	HFM/A 1.1				
Material:	Labor:				

HFM/A 1.1 HFM/A 1.1

Carry:

HFMA\_11\_AT\_EN\_V2-0 9AKK107991A0080 Rev. B