


























































Product matrix



| | Area lighting | | Area/Flood lighting | |
|----------------|---|---|---|---|
| | XSL14 LED Series p. 12 | XSL3 LED Series p. 16 | XSL11 LED Series p. 26 | XSL10 LED Series p. 32 |
| |  |  |  |  |
| Classification |  |  |  |  |
| Optics - IESNA |  |  |  |  |
| Optics - NEMA | — | — |  |  |
| IP/NEMA |  |  |  |  |
| DLC | — |  |  | — |
| Certification |  |  |  |  |
| Wattage | 40-60W | 37-138W | 107-310W | 26-57W |
| Lumen | 6,499-8,514lm | 5,600-20,000lm | 12,000-32,000lm | 3,000-6,300lm |
| Voltage | 120-277VAC, 50/60Hz 347-480VAC, 50/60Hz | 120-277VAC, 50/60Hz 347-480VAC, 50/60Hz | 120-277VAC, 50/60Hz 347-480VAC, 50/60Hz | 120-277VAC, 50/60Hz 347VAC, 60Hz |
| Dimming | — | 0-10V dimming | 0-10V dimming | 0-10V dimming |



| | Flood lighting | Linear lighting | | | | |
|----------------|---|---|---|--|---|---|
| | XFL15 LED Series p. 36 | XLN17 LED Series p. 42 | XLN17-EM LED Series p. 46 | XLN16 LED Series p. 50 | XLN13 LED Series p. 54 | XLN12 LED Series p. 58 |
| |  |  |  |  |  |  |
| Classification |  |  |  |  |  |  |
| Optics - IESNA | — |  |  |  |  |  |
| Optics - NEMA |  | — | — | — | — | — |
| IP/NEMA |  |  |  |  |  |  |
| DLC |  |  | — |  | — | — |
| Certification |  |  |  |  |  |  |
| Wattage | 80-150W | 40-80W | 80W (6W EMB) | 40-80W | 36-109W | 12-41W |
| Lumen | 10,400-19,500lm | 4,800-9,600lm | 10,800lm (812lm EMB) | 5,480-10,960lm | 4,000-10,000lm | 580-2,300lm |
| Voltage | 120-277VAC, 50/60Hz 347-480VAC, 50/60Hz | 120-277VAC, 50/60Hz 347-480VAC, 50/60Hz | 120-277VAC, 50/60Hz | 120-277VAC, 50/60Hz 347-480VAC, 50/60Hz | 120-277VAC, 50/60Hz 347-480VAC, 50/60Hz | 120VAC, 50/60Hz 12V or 24V DC |
| Dimming | — | — | — | — | 0-10V dimming | — |

¹IP68 only available with DC general location version