
TECHNICAL DATA SHEET

PMA CobotProtect™ - BCSR - Cobot Strain Relief



Applications:

- In automation applications to relief strain and to fixate individual cables/tubes to a conduit terminal

Features & Benefits:

- Fastening of individual cables/tubes to a conduit terminal via cable ties (not included)
- To be used freely rotating around conduit axis, or in “lock” mode using a BFH-0 clip (see drawing page 2)
- Fits G- and T conduit profile
- Easy to install and to exchange

Materials:

- High-grade, specially formulated polyamide 6

Compatible with:

- PMAFLEX Pro Conduits
- PMAFLEX Multilayer Conduits
- PMAFLEX Conduits
- PMA Smart Line conduits
- PMA Clip - BFH-0 - System support
- PMA Trust - BGPM - System support

Colour:

- Black

Chemical properties:

- Please refer to www.pma.ch (Technical Information / Chemical Resistance)

Additional information:

- Combining the BCSR with a BFH-0, requires a BFH-0 of the next larger NW (i.e., BCSR-17 is used in combination with BFH-23-0)





Environmental properties:

- Free from halogens and cadmium
- RoHS and REACH compliant

Product selection:

Part no.	Conduit size	Fits to BFH-0 BGPM-1x	Strain relief teeth	Dimensions in mm (nom.)		Weight	Packing unit
black	NW (B)	NW (A)	qty	A	B	kg/100 pcs	pcs/PU
BCSR-17	17	23	4	28.8	10.0	5.0	10
BCSR-23	23	29	6	28.8	10.0	6.0	10
BCSR-29	29	36	6	28.8	10.0	8.6	10

Our customer service dept. or local distribution partner will be pleased to help you concerning product availability and lead time



Mechanical Properties:	Value:	Test parameters:	Test method:
Tensile modulus	1'200 ... 3'700 N/mm ²		ISO 527
Tensile strength	45 ... 65 N/mm ²		ISO 527
Notched bar impact test	4 ... 20 kJ/m ²		ISO 180/1C

Thermal properties:	Value:	Test parameters:	Test method:
Continuous application temperature	-50 ... +105°C		PMA DO 9.21-4510
Upper application temperature	+120°C	(20'000 h)	PMA DO 9.21-4360
Short-term	+160°C	(168 h)	PMA DO 9.21-4360

Content of delivery:

- 1x BCSR, Cobot Strain Relief Ring

Assembly instructions:

- Please consider the appropriate assembly instructions on www.pma.ch

ABB Switzerland Ltd,
PMA Cable Protection
Aathalstrasse 90
8610 Uster, Switzerland
Phone: +41 58 585 00 11
pma-info@ch.abb.com
www.pma.ch

Let's write the future.
Together. **abb.com**

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Installation Products