

# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-L48139-3811-21509991-7  
**Report Reference** E48139-19990512  
**Date** 13-Dec-2022

**Issued to:** ABB Stotz-Kontakt GmbH  
Eppelheimer Str 82 Heidelberg 69123  
Germany

**This is to certify that** NKCR7 - Auxiliary Devices Certified for Canada  
**representative samples of** See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** CSA C22.2 NO. 60947-1-13, 2nd Ed., Issue Date: 2013-07-31, CSA C22.2 NO. 60947-4-1, 2nd Ed., Issue Date: 2014-04-04, Revised 2018-05

**Additional Information:** See the UL Online Certifications Directory at  
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-CA-L48139-3811-21509991-7  
**Report Reference** E48139-19990512  
**Date** 13-Dec-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
1TGB100038	Accessories, mechanical resets
B160NE	Auxiliary Devices
B90NE	Auxiliary Devices
DB140E	Accessories, mechanical resets, terminal adapters
DB16E	Accessories, mechanical resets, terminal adapters
DB19EF	Accessories, mechanical resets, terminal adapters
DB45E	Accessories, mechanical resets, terminal adapters
DB45EF	Accessories, mechanical resets, terminal adapters
DB80E	Accessories, mechanical resets, terminal adapters
DT500, for EF460.	Accessory – Bus Copper
DT800, for EF750.	Accessory – Bus Copper
E16DU, followed by -0.32, -1.0, -2.7, -6.3 or -18.9.	Overload relays, electronic, open type
E45DU, followed by -30 or -45.	Overload relays, electronic, open type
E80DU	Overload relays, electronic, open type
EF146	Overload relays, electronic, open type
EF19, followed by -0.32, -1.0, -2.7, -6.3 or -18.9.	Overload relays, electronic, open type
EF205	Overload relays, electronic, open type
EF370	Overload relays, electronic, open type
EF45, followed by -30 or -45.	Overload relays, electronic, open type
EF460	Overload relays, electronic, open type
EF65, followed by -56 or -70.	Overload relays, electronic, open type
EF750	Overload relays, electronic, open type
EF96	Overload relays, electronic, open type
EF96-100	Overload relays, electronic, open type
EF96-56	Overload relays, electronic, open type



Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-US-L48139-1811-21509991-7  
**Report Reference** E48139-19990512  
**Date** 13-Dec-2022

**Issued to:** ABB Stotz-Kontakt GmbH  
Eppelheimer Str 82 Heidelberg 69123  
Germany

**This is to certify that** NKCR - Auxiliary Devices  
**representative samples of** See Addendum Page for Product Designation(s).

Have been evaluated by UL in accordance with the  
Standard(s) indicated on this Certificate.

**Standard(s) for Safety:** UL 60947-1, 5th Ed., Issue Date: 2013-07-31, Revision  
Date: 2019-05-06, UL 60947-4-1, 3rd Ed., Issue Date:  
2014-04-04, Revision Date: 2017-10-17

**Additional Information:** See the UL Online Certifications Directory at  
<https://iq.ulprospector.com> for additional information

This Certificate of Compliance indicates that representative samples of the product described in the certification report have met the requirements for UL certification. It does not provide authorization to apply the UL Mark. Only the Authorization Page that references the Follow-Up Services Procedure for ongoing surveillance provides authorization to apply the UL Mark.

Only those products bearing the UL Mark should be considered as being UL Certified and covered under UL's Follow-Up Services.

Look for the UL Certification Mark on the product.



Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>

# CERTIFICATE OF COMPLIANCE

**Certificate Number** UL-US-L48139-1811-21509991-7  
**Report Reference** E48139-19990512  
**Date** 13-Dec-2022

This is to certify that representative samples of the product as specified on this certificate were tested according to the current UL requirements

Model	Category Description
1TGB100038	Accessories, mechanical resets
B160NE	Auxiliary Devices
B90NE	Auxiliary Devices
DB140E	Accessories, mechanical resets, terminal adapters
DB16E	Accessories, mechanical resets, terminal adapters
DB19EF	Accessories, mechanical resets, terminal adapters
DB45E	Accessories, mechanical resets, terminal adapters
DB45EF	Accessories, mechanical resets, terminal adapters
DB80E	Accessories, mechanical resets, terminal adapters
DT500, for EF460.	Accessory – Bus Copper
DT800, for EF750.	Accessory – Bus Copper
E16DU, followed by -0.32, -1.0, -2.7, -6.3 or -18.9.	Overload relays, electronic, open type
E45DU, followed by -30 or -45.	Overload relays, electronic, open type
E80DU	Overload relays, electronic, open type
EF146	Overload relays, electronic, open type
EF19, followed by -0.32, -1.0, -2.7, -6.3 or -18.9.	Overload relays, electronic, open type
EF205	Overload relays, electronic, open type
EF370	Overload relays, electronic, open type
EF45, followed by -30 or -45.	Overload relays, electronic, open type
EF460	Overload relays, electronic, open type
EF65, followed by -56 or -70.	Overload relays, electronic, open type
EF750	Overload relays, electronic, open type
EF96	Overload relays, electronic, open type
EF96-100	Overload relays, electronic, open type
EF96-56	Overload relays, electronic, open type



Deborah Jennings-Conner, VP Regulatory Services

UL LLC

Any information and documentation involving UL Mark services are provided on behalf of UL LLC (UL) or any authorized licensee of UL. For questions, please contact a local UL Customer Service Representative at <http://ul.com/aboutul/locations/>