ABB MEASUREMENT & ANALYTICS

CoriolisMaster


Accurate flow measurement of liquids and gases



CoriolisMaster
Measurement made easy

Highest measurement accuracy, easy installation and handling, compact and space-saving design

- **High-precision measurement** of mass and volume flow, density, temperature and concentration with just one device
- **Easy installation** due to a space-saving design
- **Easy reduction** of operating costs: minimal pressure loss, no moving parts and inherently maintenance-free
- **Easy integration** due to a modular transmitter concept and universal sensor design
- **Easy operation** through the standard ABB user interface
- **Inlet or outlet straight length sections** are not required





CoriolisMaster
Top performance


Accurate measurement – optimal design

The excellent zero stability enables measuring spans of 100:1 or larger. Top measuring accuracy has been confirmed and certified by independent bodies.

ABB offers a variety of models with different accuracy and designs. Selectable accuracy classes allow for optimal tailoring to the required process conditions. Installation length and handling are identical for all models. The large tube diameter minimizes pressure losses to virtually zero, allowing for up to 50% pressure loss savings compared to other commercially available products.










CoriolisMaster
The sensors

The ideal combination of performance, compact size and low pressure drop



Maintenance-free design
No moving parts in the fluid makes the design of the CoriolisMaster inherently maintenance-free.

Self-draining sensor design
No fluid or solid residues remain in the tubes.

FCBxxx: Universal Sensor
Featuring high savings potential for installation, lower required pump capacity and spare part costs. Compact size with low tare weight.

FCHxxx: Sensor for hygienic applications
The same advantages as the FCBxxx, additionally with EHEDG certification.



—
FCBxxx



—
FCHxxx

CoriolisMaster
The transmitters

Comes with a variety of transmitters that are tailored for specific applications

FCx100 – System integration flowmeter
The FCx100 transmitter is specifically designed to make system integration as easy as possible. It features a high speed Modbus RS485 output and additional digital outputs. This allows for easy and complete system integration with the measuring device even for quick filling applications.

FCx400 – Flowmeter with high-performance signal transmitter
The transmitter features up to five inputs/outputs. The modular concept offers maximum flexibility. Its sensor and application memory concept enables easy maintenance and utmost data security. Thanks to the digital SmartSensor technology, industry-standard cables can be used with remote mount technology.

—
FCx400 transmitter in single-compartment housing for remote mount design



—
FCx400 transmitter in dual-compartment housing for remote mount design



—
FCx100 transmitter for integral mount design





—
FCx400 transmitter in single-compartment housing for integral mount design



—
FCx400 transmitter in dual-compartment housing for integral mount design

CoriolisMaster
The modular concept

Up to 5 modular inputs/ outputs
- Optimal tailoring to the application
- Various digital communication protocols available

Digital SmartSensor technology
- Easy installation, industry-standard cables can be used for the remote mount design
- Intelligence of measuring devices close to the sensor

SensorApplicationMemory
- Maximum data security
- Plug and play replacement of transmitter electronic components

Common ABB look and feel
- Quick commissioning with the Easy Set-up functionality
- Intuitive operation through the front glass using capacitive buttons

Enhanced Coriolis Control (ECC)
- Functionality for enhanced performance under multiphase conditions and for challenging fluids

Integrated VeriMass Device verification and diagnosis
- Predictive maintenance
- Extended maintenance cycles

CoriolisMaster Software Tools
- DensiMass for concentration measurement, net mass and volume flow measurements
- FillMass for filling applications

For robust operating conditions
- Designed for ambient temperatures of up to 70°C
- Resistant to high vibration

VeriMass
Integrated device verification and diagnosis

Comprehensive diagnosis in accordance with NAMUR standard NE107 is included in the base version. VeriMass offers more. The built-in erosion monitoring function creates a “fingerprint” of the measuring device in the specific application as a basis for automatic, continuous monitoring. As this feature focuses on erosion and coating of the meter, long term trends are identified.

The health status of the meter as well as the erosion monitor status can be combined in a verification report print out, documenting required meter checks.

—
Diagnosis and VeriMass verification with the ABB Ability Verification SRV500 solution



CoriolisMaster
Maximum versatility

Functional safety, special application software and extensive approvals – you can't ask for more.

Functional safety
The CoriolisMaster FCx400 devices are certified in accordance with SIL2 and therefore offer the highest safety standards. The special advantage of the CoriolisMaster technology is that the required proof tests can be conducted on-site without the need to remove the device.

DensiMass software
With the integrated DensiMass software, direct concentration measurements, Brix measurements or net oil calculations (water content) are possible. Even temperature-standardized calculations of density and volume, based on the extensive database stored in the measuring device, can be conducted.

FillMass Software
With the help of the integrated FillMass software, an independent filling function can be implemented. It allows for the direct control of the filling valve.

Enhanced Coriolis Control (ECC) option
Innovative control algorithms for Coriolis meter operation enhances the flow and density measurement under multiphase conditions or with challenging fluids.





CoriolisMaster
The portfolio at a glance

Sensor*	Transmitter
FCBxxx Standard	FCx100 – Modbus transmitter for integral mount design
	
	FCx400 – Top performance transmitter for integral mount design
	
FCHxxx Hygienic	FCx400 – Sensor electronics for remote mount design
	
	FCx400 – Top performance transmitter for remote mount design
	

*Available only together with transmitters

CoriolisMaster
Simply fits your purpose

The most important data at a glance		
Nominal sizes		
DN 15	(FCBxxx)	0 … 8,000 kg/h
DN 25	(FCBxxx/FCHxxx)	0 … 35,000 kg/h
DN 50	(FCBxxx/FCHxxx)	0 … 90,000 kg/h
DN 80	(FCBxxx/FCHxxx)	0 … 250,000 kg/h
DN 100	(FCBxxx)	0 … 520,000 kg/h
DN 150	(FCBxxx)	0 … 860,000 kg/h
Wetted materials 1.4404/1.4435 (316L) or Hastelloy C		

CoriolisMaster FCXx30	CoriolisMaster FCXx50
Accuracy for liquids	
Mass: 0.4 % / 0.2 % o.r.	Mass: 0.15 % / 0.1 % o.r.
Volumes: 0.4 % / 0.2 % o.r.	Volumes: 0.15 % / 0.11 % o.r.
Density: 0.01kg/m³	Density: 0.002kg/m³; 0.001kg/m³ or 0.0005kg/m³ as option
Accuracy for gases	
Mass: 1 % o.r.	Mass: 0.5 % o.r.
Measured medium temperature	
-50 … 160 °C	-50 … 205 °C

Approvals	
Explosion protection	IECEx, ATEX, cFMus, NEPSI Zone 0,1,2 or Div. 1,2
Marine, Offshore	DNV GL BV, CCS
Custody transfer	API, chapter 5.6 and AGA11, OIML R117; MID approved
Hygienic applications	FDA material conformity
Mechanical safety	PED, CRN and NACE
Functional safety	TÜV SIL2 Certificate

	Series FCx100	Series FCx400
		
LCD indicator	no	yes, illuminated
Outputs	Modbus 2 digital outputs (impulse, frequency contact output)	Up to 5 modular inputs/outputs freely selectable and adjustable*, HART, Modbus RTU, PROFIBUS DP, Ethernet IP, Modbus TCP, Webserver
Operation possible without opening the cover	no	yes
SmartSensor Concept	yes	yes
Ambient temperature	-40 … 70 °C	-40 … 70 °C
Custody transfer	yes, in accordance with MID/OIML R175	yes, in accordance with MID/OIML R175
SIL2	no	yes
Power supply	11 … 30 VDC	11 … 30 VDC 110/230 VAC
Max. power consumption	5 W (normal: 2… 3 W)	20 W (normal: 4 … 5 W)
DensiMass concentration	yes (Version FCx150)	yes (Version FCx450)
FillMass filling software	yes (Version FCx150)	yes (Version FCx450)
VeriMass verification	yes	yes

*Details available in the data sheet





Contact

ABB Ltd.
Measurement & Analytics

www.abb.com/measurement

© Copyright 2022 ABB. All rights reserved.
Specifications subject to change without notice.

LFT/CORIOLISMASTER_CT-EN REV A 06.2022