1. # CERTIFICATE

2. ## VTT No. Ex-10.016X Issue 4

3. This Certificate is issued for the following electrical apparatus, intended for use in potentially explosive atmospheres:

4. Equipment: **Range of cage induction motors**

   Certified types: **AMI 400...**
   AMI 450...
   AMI 500...

5. Applicant : **ABB Oy Motors and Generators**
   Strömbergintie 1
   FI-00380 Helsinki
   Finland

6. Manufactured by **ABB Oy Motors and Generators**
   Hiomotie 13
   FI-00380 Helsinki
   Finland
   or
   ABB Electrical Machines Ltd
   No. 380, Tian Xing Road
   Minhang District, Shanghai
   People's Republic of China
   or
   ABB India Limited
   Maneja Village
   390013, Vadodara, Gujarat
   India

7. These electrical apparatus and any acceptable variations thereto are specified in the Annex and possible supplement(s) to this Certificate and in the descriptive documents therein referred to.

8. VTT Expert Services Ltd, Certification Body No. S017 accredited by the Finnish Accreditation Service (FINAS),

- certifies that these electrical apparatus has been found to comply with the following IEC-standards:

  IEC 60079-0 (2011)
  IEC 60079-7 (2015)

  and have successfully met the type verification and test requirements of these standards.

- confirms that confidential Research Report VTT-S-06614-17 has been completed on these verifications and tests.

9. The code for the electrical apparatus is:

Ex ec IIA/IIB/IIC T1-T4 Gc

10. By marking the supplied electrical apparatus, the manufacturer attests on his own responsibility that this electrical apparatus complies with the descriptive documents referred to in the Annex to this Certificate or in the Research Report.

11. If there appears sign X after the certification number, there are special conditions for safe use, which are specified in the Annex of this Certificate.

Espoo, 11.12.2017

VTT Expert Services Ltd

Martti Siirola
Senior Expert

Jenni Hirvelä
Expert

Certificate without signatures shall not be valid.
This certificate, including the annex may only be reproduced in its entirety and without any change.

Range of cage induction motors, types AMI 400, AMI 450 or AMI 500

Description of Equipment

Three phase squirrel cage induction motors of a closed type with welded steel frame. The mounting can be horizontal or vertical. The motors are fitted out with Ex-certified main terminal boxes and Ex-certified auxiliary terminal boxes. The temperature class of the motor depends on the ratings of the motor and temperature class of the accessories. Auxiliary device options, including the terminal boxes, are listed in Annex A of this Certificate.

Technical data

The equipment is intended for both direct-on-line (DOL) and variable speed drive (VSD) supply. The Certificate is valid for the range of induction motors having shaft heights 400, 450 or 500 and the electrical values within the limits in the following table:

U / kV	Number of poles	f or n	P / kW
Up to 11,5	2 - 20	50/60 Hz (DOL) 0…4500 rpm (VSD)	Up to 4000

The duty type of the motors shall be S1, S2, S6 or S9.

17. Report No. VTT-S-06614-17

18. Special conditions for safe use

The allowed ambient temperature range of a motor depends on the design and auxiliary devices. The allowed ambient temperature range of each motor is marked on the rating plate. The marked ambient temperature is always within the range of -50 °C…+60 °C.

Temperature class may vary between T1 - T4 depending of the design. The temperature class of each motor is marked on the rating plate.

Depending of the equipment groups of the auxiliary devices, the equipment group may be IIA, IIB or IIC. The equipment group of each motor is marked on the rating plate.

Certificate without signatures shall not be valid.
This certificate, including the annex may only be reproduced in its entirety and without any change.

The special conditions in the Certificates of the separately certified auxiliary devices shall be conformed to.

The equipment may present a potential electrostatic charging hazard due to paint; the manufacturer's instructions shall be followed in order to minimize the risk of electrostatic discharge.

If the motor is intended for VSD supply, the motor will be marked accordingly and the following conditions apply:

The allowed VSD is marked on the rating plate and it is part of the following series manufactured by ABB Group Ltd: ACS 600, ACS 800, ACS 880, ACS 1000, ACS 2000 or ACS 5000.

The 2-level low voltage ($\leq$ 1 kV) voltage source converter types shall fulfil the following converter requirements determined at motor terminals:
- Switching frequency min. average 3 kHz (2.65 kHz for DTC®-control)
- Common mode (CM) voltage max. 500 V
- When installed, common mode voltage rise time du_{CM}/dt max. 70 V/µs.

Also other 2-level low voltage ($\leq$ 1 kV) voltage source converter types not manufactured by ABB Group Ltd may be used if the above mentioned converter requirements are fulfilled.

The allowed speed and torque ranges of each motor are marked on the rating plate and all manufacturer's instructions shall be followed.

Thermal protection of the motor at VSD supply is based on the torque limiting function of the VSD and the resistance thermometers in the stator windings of the motor.

Certificate history

Issue	Date	Report No.	Comment
-	15.4.2010	VTT-S-03059-10	Prime certificate
1	28.2.2012	VTT-S-01545-12	Change of the applicant's name. Certification documents are updated with new tests results and construction changes especially with main terminal boxes. Use with the converter type ACS 2000 added. The certificate is extended to cover the new standards IEC 60079-0 (2011) and EN 60079-15 (2010)
2	21.10.2016	VTT-S-04443-16	Converter series ACS 880 added.

Certificate without signatures shall not be valid.
This certificate, including the annex may only be reproduced in its entirety and without any change.

3	29.12.2016	VTT-S-04812-16	Updated to the latest edition of IEC 60079-7 and the marking has been changed to "ec" accordingly. Documents have been updated. Special conditions for safe use have been updated. Duty types S6 and S9 have been added. List of Auxiliary devices has been updated and added on the certificate.
4	11.12.2017	VTT-S-06614-17	Structural changes in grounding and air-water heat exchanger. List of Auxiliary devices has been updated. Document updates.

Espoo, 11.12.2017

VTT Expert Services Ltd

Martti Siirola
Senior Expert

Jenni Hirvelä
Expert

Certificate without signatures shall not be valid.
This certificate, including the annex may only be reproduced in its entirety and without any change.

ANNEX A TO TYPE EXAMINATION CERTIFICATE NO. VTT No. Ex-10.016X Issue 4

LIST OF AUXILIARY DEVICES

Component	Manufacturer	Marking	ABB standard number or drawing	ATEX / IECEx certificate	Notes
3300 XL 8 mm Proximity transducer system for sleeve bearing for measuring vibration, Amplifier, Proximitor sensor	Bently Nevada	II 1 G EEx ia IIC T4/T5 Class I Zone 0, Class I Div 1 Groups ABCD	PXM XYKPA5	BAS 99 ATEX 1101 IECEx BAS 04.0055X	
3300 XL 8 mm Proximity transducer system for sleeve bearing for measuring vibration, Amplifier, Proximitor sensor	Bently Nevada	II 3G Ex nA IIC T4/T5 Class I Zone 2, Class I Div 2 Groups ABCD	PXM XYKPA5	Baseefa 07 ATEX 0189X IECEx BAS 04.0057X	
Accelerometer for vibration monitoring, type 330400-02-05	Bently Nevada	II 3 G Ex nA IIC T4 Gc II 3 D Ex tc IIIC T130°C Dc II 1 G Ex ia IIC T4 Ga	PYM 330400EX	II 3 G Ex nA IIC T4 Gc II 3 D Ex tc IIIC T130°C Dc IECEx LCI 06.0002X, LCIE 04 ATEX 6041X Ex ia IIC T4 Ga IECEx LCI 06.0003X, LCIE 04 ATEX 6042X	
Anticondensation heater, type CP... therm D... T...	Intertec	II 2 G Ex db IIC T3/T4 II 2 D Ex tb IIIC IP65 T200°C/T135°C	None	IECEx PTB 07.0052X PTB 02 ATEX 1041 X	
Anticondensation heater, type SL... therm D... T...	Intertec	II 2 G Ex db IIC T3/T4 II 2 D Ex tb IIIC IP65 T200°C/T135°C	REX 50, REX 80 and REX 200	IECEx PTB 07.0055X PTB 02 ATEX 1116 X	
Auxiliary terminal box, equipped, types ZWA EX_ (types Fibox ALNX... and Rose 25...)	ABB Oy	II 2 G Ex e IIC T4 Gb II 2 D Ex tb IIIC T105°C Db IP66		IECEx VTT 12.0003X VTT 12 ATEX 013X	
Auxiliary terminal box, equipped, types ZWA EX_ (types Fibox ALNX... and Rose 25...)	ABB Oy	II 2 G Ex e ia IIC T4 Gb II 2 D Ex tb IIIC T105°C Db IP66		IECEx VTT 12.0004X VTT 12 ATEX 014X	
Auxiliary terminal box, equipped, types ZWA EX_ (types Fibox ALNX... and Rose 25...)	ABB Oy	II 2 G Ex ia IIC T4 Gb II 2 D Ex tb IIIC T105°C Db IP66		IECEx VTT 12.0005X VTT 12 ATEX 015X	
Auxiliary terminal box, equipped, types ZWA EX_ (types Fibox ALNX... and Rose 25...)	ABB Oy	II 3 G Ex nA IIC T4 Gc II 3 D Ex tc IIIC T105°C Dc IP66		IECEx VTT 12.0006X VTT 12 ATEX 016X	
Auxiliary terminal box, equipped, Type DAAM_AUX_	ABB Oy	II 2 G Ex e IIC T4 Gb	DAAM_AUX200BS DAAM_AUX200SS DAAM_AUX325BS DAAM_AUX325SS DAAM_AUX325BSW DAAM_AUX325SSW DAAM_AUX500BS DAAM_AUX500SS	VTT 06 ATEX 011X	
Auxiliary terminal box, equipped, Type DAAM_AUX_	ABB Oy	II 2 G Ex e ia IIC T4 Gb	DAAM_AUX200BS DAAM_AUX200SS DAAM_AUX325BS DAAM_AUX325SS DAAM_AUX325BSW DAAM_AUX325SSW DAAM_AUX500BS DAAM_AUX500SS	VTT 06 ATEX 012X	
Auxiliary terminal box, equipped, Type DAAM_AUX_	ABB Oy	II 2 G Ex ia IIC T4 Gb	DAAM_AUX200BS DAAM_AUX200SS DAAM_AUX325BS DAAM_AUX325SS DAAM_AUX325BSW DAAM_AUX325SSW DAAM_AUX500BS DAAM_AUX500SS	VTT 06 ATEX 013X	

Certificate without signatures shall not be valid.
This certificate, including the annex may only be reproduced in its entirety and without any change.

Component	Manufacturer	Marking	ABB standard number or drawing	ATEX / IECEx certificate	Notes
Auxiliary terminal box, equipped, Type DAAM_AUX_	ABB Oy	II 3 G Ex nA IIC T4 Gc II 3 D Ex tc IIIB T100°C Dc, IP56	DAAM_AUX200BS DAAM_AUX200SS DAAM_AUX325BS DAAM_AUX325SS DAAM_AUX325BSW DAAM_AUX325SSW DAAM_AUX500BS DAAM_AUX500SS	VTT 06 ATEX 014X	
Auxiliary terminal box, equipped, types ZWT1_ (Rose types 34.... or Ensto Cubo X...)	ABB Oy	II 2 G Ex e IIC T4 Gb II 2 D Ex tb IIIC T100°C Db, IP66	ZWT1 AMI202012-1BS ZWT1 AMI202012-1SS ZWT1 AMI323220-1BS ZWT1 AMI323220-1SS ZWT1 AMI323223-1BW ZWT1 AMI323223-1SW ZWT1 AMI505020-2BS ZWT1 AMI505020-2SS	IECEx VTT 14.0018X VTT 06 ATEX 011X	
Auxiliary terminal box, equipped, types ZWT1_ (Rose types 34.... or Ensto Cubo X...)	ABB Oy	II 2 G Ex e ia IIC T4 Gb II 2 D Ex tb IIIC T100°C Db, IP66	ZWT1 AMI202012-1BS ZWT1 AMI202012-1SS ZWT1 AMI323220-1BS ZWT1 AMI323220-1SS ZWT1 AMI323223-1BW ZWT1 AMI323223-1SW ZWT1 AMI505020-2BS ZWT1 AMI505020-2SS	IECEx VTT 14.0019X VTT 06 ATEX 012X	
Auxiliary terminal box, equipped, types ZWT1_ (Rose types 34.... or Ensto Cubo X...)	ABB Oy	II 2 G Ex ia IIC T4 Gb II 2 D Ex tb IIIC T100°C Db, IP66	ZWT1 AMI202012-1BS ZWT1 AMI202012-1SS ZWT1 AMI323220-1BS ZWT1 AMI323220-1SS ZWT1 AMI323223-1BW ZWT1 AMI323223-1SW ZWT1 AMI505020-2BS ZWT1 AMI505020-2SS	IECEx VTT 14.0020X VTT 06 ATEX 013X	
Auxiliary terminal box, equipped, types ZWT1_ (Rose types 34.... or Ensto Cubo X...)	ABB Oy	II 3 G Ex nA IIC T4 Gc II 3 D Ex tc IIIC T100°C Dc, IP66	ZWT1 AMI202012-1BS ZWT1 AMI202012-1SS ZWT1 AMI323220-1BS ZWT1 AMI323220-1SS ZWT1 AMI323223-1BW ZWT1 AMI323223-1SW ZWT1 AMI505020-2BS ZWT1 AMI505020-2SS	IECEx VTT 14.0021X VTT 06 ATEX 014X	
Auxiliary terminal box, stainless steel / steel, type 35... or 36...	ROSE Systemtechnik GmbH	Ex d e ia [ia] mb IIC T6, T5, T4 Gb Ex tb IIIC T 85 °C, T 100 °C, T135 °C Db	ZWT AISI200x200 ZWT AISI300x300 ZWT TEFX10581511 ZWT TEFX10582511 ZWT TEFX10583011 ZWT TEFX10591010	IECEx PTB 07.0060 PTB 00 ATEX 1052	
Auxiliary terminal box, stainless steel equipped, types ZWT TEFX..., (Rose types 34..., Tranberg types 1058 and 1059, and Cooper N-TB)	ABB Oy	II 2 G Ex eb IIC T4 Gb II 2 D Ex tb IIIC T100°C Db, IP66 ZWT TEFX105...: II 2 G Ex eb IIC T4 Gb	ZWT TEFX34... ZWT TEFXN... ZWT TEFX105...	IECEx VTT 17.0006X VTT 11 ATEX 020X	
Auxiliary terminal box, stainless steel equipped, types ZWT TEFX..., (Rose types 34..., Tranberg types 1058 and 1059, and Cooper N-TB)	ABB Oy	II 2 G Ex eb ia IIC T4 Gb II 2 D Ex tb IIIC T100°C Db, IP66 ZWT TEFX105...: II 2 G Ex eb ia IIC T4 Gb	ZWT TEFX34... ZWT TEFXN... ZWT TEFX105...	IECEx VTT 17.0007X VTT 11 ATEX 021X	
Auxiliary terminal box, stainless steel equipped, types ZWT TEFX..., (Rose types 34..., Tranberg types 1058 and 1059, and Cooper N-TB)	ABB Oy	II 2 G Ex ia IIC T4 Gb II 2 D Ex tb IIIC T100°C Db, IP66 ZWT TEFX105...: II 2 G Ex ia IIC T4 Gb	ZWT TEFX34... ZWT TEFXN... ZWT TEFX105...	IECEx VTT 17.0008X VTT 11 ATEX 022X	

Certificate without signatures shall not be valid.
This certificate, including the annex may only be reproduced in its entirety and without any change.

Component	Manufacturer	Marking	ABB standard number or drawing	ATEX / IECEx certificate	Notes
Auxiliary terminal box, stainless steel equipped, types ZWT TEFX..., (Rose types 34..., Tranberg types 1058 and 1059, and Cooper N-TB)	ABB Oy	II 3 G Ex ec IIC T4 Gc II 3 D Ex tc IIIC T100°C Dc, IP66 ZWT TEFX105...: II 3 G Ex ec IIC T4 Gc	ZWT TEFX34... ZWT TEFXN... ZWT TEFX105...	IECEx VTT 17.0009X VTT 11 ATEX 023X	
Auxiliary terminal box, type NXT	Cooper Crouse Hinds	II 2G EEx e II T6/T5 or II 1G EEx ia IIC T6/T5 or II 2 (1) G EEx e (ia) IIC T6/T5 II 2D T100°C	None	IECEx BKI 08.0010 KEMA 99 ATEX 3172X	
Auxiliary terminal box, type TNCN	Technor ASA	Ex eb IIC T4/T5/T6 Gb Ex tD A21 IP66-68 T80°C-110°C	None	DNV 2001 OSL ATEX 0176 IECEx DNV 09.0004	
Auxiliary terminal box, types 8125/1 or 8125/2	Stahl	Ex d e ia ib [ia Ga] mb IIA, IIB, IIC T6, T5, T4 Gb or Ex db eb ia ib [ia] mb IIA, IIB, IIC T6, T5, T4 Ex tb IIIC T80 °C, T95 °C, T130 °C Db or Ex tb IIIC T80 °C, T95 °C, T130 °C	None	PTB 00 ATEX 3116 IECEx PTB 06.0060	
Auxiliary terminal box, types GHG 74...	Cooper Crouse-Hinds GmbH	II 2 G /D EEx d e ia/ib m [ia/ib] IIC T4-T6 IP66 T 80°C Ex e* IIC T4 / T5 / T6 Gb Ex tb IIIC T80°C / T95°C Db * Optional the marking can be amplified with the types of protection of the separately certified components, for example "d", "e", "mb" and/or "ia/ib".	None	IECEx BVS 12.0071X PTB 99 ATEX 1044	
Auxiliary terminal box, types GHG 72...	Cooper Crouse-Hinds GmbH	Ex e * IIC T4 / T5 / T6 Gb Ex tb IIIC T80°C / T95°C Db *) Optional the marking can be amplified with the types of protection of the separately certified components, for example "d" and/or "ib".	None	IECEx BVS 13.0031X PTB 99 ATEX 1044	
Auxiliary terminal box type 06.****** and 16.******, types Polyester-KE 06..., Polyester-KE 16..., ROSE 06.12 22 09 and ROSE 06.14 12 00	ROSE Systemtechnik GmbH	Ex d e ia [ia] mb IIC T6, T5, T4 Gb Ex tb IIIC T85 °C, T100 °C, T135 °C Db	ZWM PE 120x220 ZWM PE 270x270	IECEx PTB 08.0004 PTB 00 ATEX 1002	
Blind plug for cable gland, type HSK-V-Ex	Hummel AG	Ex e IIC Gb Ex ta IIIC Da	MRR HSK-EX...	IECEx BVS 07.0022X BVS 03 ATEX E 298	
Cable gland, Anamet, Type R... or B...	RCN s.r.l.	Ex d I , Ex e I, Ex d IIC Gb, Ex e IIC Gb and Ex tb IIIC Db IP66 or IP66/68	MRR ST-EX-	IECEx INE 10.0010X INERIS 06 ATEX 0014X	
Cable gland, type 501/414...	Hawke	II 2 G Ex e IIC Gb, Ex d IIC Gb II 2 D Ex tb IIIC Db IP66	MRR MMTH3-...	IECEx BAS 06.0013X Baseefa 06 ATEX 0056X	
Cable gland, type 501/421	Hawke	II 2 G Ex e IIC Gb, Ex d IIC Gb II 2 D Ex tb IIIC Db IP66	MRR HAW2-...-...	IECEx BAS 06.0013X Baseefa 06 ATEX 0056X	
Cable gland, type 501/453/Universal	Hawke	II 2 G Ex e IIC Gb, Ex d IIC Gb II 2 D Ex tb IIIC Db IP66	MRR HAW1-...-...	(Size Os to F) IECEx BAS 06.0014X Baseefa 06ATEX0057X (Size G to J): IECEx BAS 06.0013X Baseefa 06 ATEX 0056X	
Cable gland, type HSK-K-Ex	Hummel AG	II 2GD EEx e II IP68 Ex tD A20 IP68	MRR PMT-EX-...	IECEx BVS 07.0020X DMT 02 ATEX E 047 X	

Component	Manufacturer	Marking	ABB standard number or drawing	ATEX / IECEx certificate	Notes
Cable gland, type HSK-M-EMV-Ex 1.616.****.**	Hummel AG	II 2G Ex e II II 1D Ex tD A20 IP68	None	IECEx BVS 07.0019X DMT 03 ATEX E 051 X	
Cable gland, type HSK-M-EMV-Ex 1.646.****.**	Hummel AG	II 2 G Ex e IIC Gb II 1 D Ex ta IIIC Da	MRR MMT-EX-...-.../...	IECEx KEM 07.0014X KEMA 99 ATEX 6971 X	
Dial type analog thermometer for bearing and cooling air, type 822E 6BS	United Electric Controls	II 2 G EEx d IIC T6 II 2 D T+85°C IP 66 Class I, Division 1 and 2, Groups B, C & D Class II, Division 1 and 2, Groups E, F & G Class III Class I, Zone 1, Group IIB + H2 T6	UCW LK822EX	DEMKO 03 ATEX 0305048 IECEx UL 03.0001	
Drain plug for auxiliary terminal boxes, series 8162...	Stahl	II 2 G Ex e II II 2 D Ex tD A21 IP66 or IP64 Ex eb IIC Gb Ex tb III C Db	MRR DPP1	PTB 01 ATEX 1018 IECEx PTB 06.0028	
Drain plug, type 730	Tranberg	II 2 G EEx e II	None	IECEx NEM 11.0006 NEMKO 02 ATEX 167	
Drain plug, type CV	Raxton	Ex e IIC Gb, Ex tb IIIC Db	None	IECEx SIR 09.0096U SIRA 00 ATEX 3074U	
Drain plug, types ACDP	Peppers (manufacturer Redapt)	II 1D 2G Ex eb IIC Gb Ex ta IIIC Da IP66	MRR DPP-EX...	SIRA 09 ATEX 3321X IECEx SIR 09.0132X	
Eddy current probe for series 3300, 7200 and 190 for sleeve bearing for measuring vibration, 3300 XL 8 mm Proximity transducer system	Bently Nevada	Ex ia IIC T1...T5 Ga Ex nA IIC T1...T5 Gc	PXM XYKPP5	IECEx BAS 04.0056 IECEx BAS 04.0058X BAS 99 ATEX 1099 BAS 99 ATEX 3098X	
Fan motors, types M3JP/KP 80-450	ABB	Ex d or Ex de IIC T3 to T6 Gb Ex t IIIC T125°C Db	None	IECEx LCI 04.0029X IECEx LCI 04.0030X IECEx LCI 04.0031X IECEx LCI 04.0009X IECEx LCI 09.0008X IECEx LCI 09.0009X IECEx LCI 04.0011X IECEx LCI 04.0005X IECEx LCI 04.0012X IECEx LCI 04.0006X IECEx LCI 04.0007X IECEx LCI 04.0008X IECEx LCI 04.0032X IECEx LCI 11.0023X	
Fan motors, types M3GP 71-450	ABB	Ex nA IIC T3 Gc Ex tc IIIB T125°C Dc	None	IECEx VTT 12.0010X IECEx LCI 07.0001X IECEx LCI 09.0012X IECEx LCI 07.0001X	
Flowmeter for air-to-water cooler, type Vortex Flowmeter Model 8800D	Rosemount Inc.	II 1 G Ex ia IIC T4 Ga (-60°C ≤ Ta ≤ +60°C)	None	IECEx BAS 05.0028X Baseefa05ATEX0084	
Incremental encoder, type 841	Leine & Linde	Ex db IIC T6...T4, Ex tb IIIC T85C...T135C	PXB L&L-EX-...	IECEx SP 06.0001X SP 07 ATEX 3635X	
Incremental encoder, type EEx OG 9...	Baumer Hübner GmbH	II 2 G Ex db eb IIC T5/T6 Gb	PXB HÜBNER OG9-1024 PXB HÜBNER OG9-2048	IECEx TUN 11.0021X TÜV 02 ATEX 1922 X	
Isolating switching amplifier for leakage sensor, types N-132/...	Rechner Industrie-elektronik	II (1) G [Ex ia] IIC II (1) D [Ex ia] IIIC	PAJ ISA-...-EX	IECEx BVS 10.0088X BVS 09 ATEX E 087X	
Measuring transducer, type TTR200 and TTR300	ABB Automation Products GmbH	II 1 G Ex ia IIC T6 Ga II 2(1) G Ex [ia] ib IIC T6 Gb (Ga) II 2 G (1D) Ex [iaD] ib IIC T6 Gb (Da)	None	IECEx PTB 09.0014X PTB 05 ATEX 2017X	
PD Trac monitoring system	Iris Power	Ex nA II T3, Ex nC IIC T3	None	IECEx UL 10.0050X IECEx UL 12.0010X DEMKO 09 ATEX 143404X	
Phase segregated main terminal box, type PSE	Quartzelec limited	II 2 G Ex e IIC Gb Ex tc IIIC IP66 Dc	None	IECEx SIR 10.0147U SIRA 03 ATEX 3222 U	

Certificate without signatures shall not be valid.
This certificate, including the annex may only be reproduced in its entirety and without any change.

Component	Manufacturer	Marking	ABB standard number or drawing	ATEX / IECEx certificate	Notes
Phase segregated main terminal box, type PSN	Quartzelec limited	II 3 G Ex nA IIC Gc Ex tc IIIC IP66 Dc	None	IECEx SIR 10.0146U SIRA 03 ATEX 4223 U	
Pressure difference switch for condition monitoring of the air filters, type AFS-293	Cleveland Controls	-	UDA AFS293	Has to be connected to Ex i circuit	
Pressure transmitter, Model 3051C	Rosemount	II 1 G Ex ia IIC T4 Ga (-60°C ≤Ta ≤+70°C) II 1 D Ex ta IIIC T50°C T50060°C Da IP66	None	BAS 97 ATEX 1089X Ex nA: IECEx BAS 09.0077X IECEx BAS 09.0076X	
Proximity transducer PROXPAC for sleeve bearing for measuring vibration, vibration phase angle and rotation speed	Bently Nevada	II 1 G EEx ia IIC T5/T6 Class I Groups A, B, C, D; Class II Groups E, F, G; Class III; ClassI Div 2 non-incendive	PXM BN2	IECEx BAS04.0055X LCIE 98 ATEX 6011 X	
Proximity transducer system for sleeve bearings, probe and extension cable	Bently Nevada	II 1 G EEx ia IIC T5	PXM XYKPC4 PXM XYKPP9	IECEx BAS 04.0056 BAS 99 ATEX 1099	
Proximity transducer system for sleeve bearings, probe and extension cable	Bently Nevada	II 3 G EEx nA II T5	PXM XYKPC4 PXM XYKPP9	IECEx BAS 04.0058X BAS 99 ATEX 3098X	
Proximity transducer system for sleeve bearings,amplifier	Bently Nevada	II 1 G EEx ia IIC T4/T5	PXM XYKPA9	IECEx BAS04.0055X BAS 99 ATEX 1101	
Proximity transducer system for sleeve bearings,amplifier	Bently Nevada	II 3G Ex nA IIC T4/T5	PXM XYKPA9	IECEx BAS 04.0057X Baseefa 07 ATEX 0189X	
Pt-100 for antifriction bearing, type WTH 280-400	H. Heinz Messwiderstände GmbH	II 2 G Ex mb IIC Gb II 2 G Ex ib IIC Gb II 1 G Ex ia IIC Ga	3GZF364130-3	IECEx IBE 15.0026U IBExU16ATEX1026 U	
Pt-100 for antifriction bearing, types PR-SPA-EX-***	Ephy-Mess GmbH	II 2G Ex e IIC Gb or 2G Ex eb IIC II 2D Ex ta IIIC Da II 2G Ex ia IIC Gb II 2D Ex ia IIIC Db -55°C≤Ta≤175°C	PYR 2PT100...EX PYR PT100...EX	IBExU 14 ATEX 1281 U IECEx IBE 14.0058 U	
Pt-100 for antifriction bearing, types SKS 1059616 WT-BAJONETTI-6/XXX-YYY/TDT-4J-KLA-EX	SKS Group Oy	II 2 G Ex e IIC T6...T3 II 2 D Ex tb IIIC T60°C...T200°C Db	PYR PT100BB5/4ZEX	VTT 14 ATEX 005X IECEx VTT 14.0003X	
Pt-100 for antifriction bearing, types SKS 1059620 2XWT-BAJONETTI-8/XXX-YYY/TDT-4J-KLA-EX	SKS Group Oy	II 2 G Ex e IIC T6...T3 II 2 D Ex tb IIIC T60°C...T200°C Db	PYR 2PT100BB5/4ZEX	VTT 14 ATEX 005X IECEx VTT 14.0003X	
Pt-100 for sleeve bearing and cooling air, types PR-SPA-EX-***	Ephy-Mess GmbH	II 2G Ex e IIC Gb or 2G Ex eb IIC II 2D Ex ta IIIC Da II 2G Ex ia IIC Gb II 2D Ex ia IIIC Db -55°C≤Ta≤175°C	PYR 2PT100...EX PYR PT100PG5/4ZEX PYR 2PT100PF5/4ZEX PYR PT100PF5/4ZEX	IBExU 14 ATEX 1281 U IECEx IBE 14.0058 U	
Pt-100 for sleeve bearing and cooling air, types SKS 1061957 WT-KAAPELI-6/XXX-YYY/TDT-4J-KLA-EX	SKS Group Oy	II 2 G Ex e IIC T6...T3 Gb, II 2 D Ex tb IIIC T60°C...T200°C Db	PYR PT100PF5/4ZEX PYR PT100PG5/4ZEX	VTT 14 ATEX 004X IECEx VTT 14.0002X	
Pt-100 for sleeve bearing and cooling air, types SKS 1061961 2XWT-KAAPELI-6/XXX-YYY/TDT-4J-KLA-EX	SKS Group Oy	II 2 G Ex e IIC T6...T3 Gb, II 2 D Ex tb IIIC T60°C...T200°C Db	PYR 2PT100PF5/4ZEX PYR 2PT100PG6/4ZEX	VTT 14 ATEX 004X IECEx VTT 14.0002X	
Pt-100 for winding fitted in winding end, type PYRA 8G	H. Heinz Messwiderstände GmbH	II 2 G Ex eb IIC Gb II 2 G Ex ib IIC Gb II 1 G Ex ia IIC Ga	None	IECEx IBE 15.0026U IBExU16ATEX1026 U	
Pt-100 for winding fitted in winding end, type PYRA 8K	H. Heinz Messwiderstände GmbH	II 2 G Ex eb IIC Gb II 2 G Ex ib IIC Gb II 1 G Ex ia IIC Ga	PYR PT100HA4/4EX PYR PT1000HA4/4EX PYR PT1000HA4/4ZEX	IECEx IBE 15.0026U IBExU16ATEX1026 U	
Pt-100 for winding, type NWT 200G	H. Heinz Messwiderstände	II 2 G Ex eb IIC Gb II 2 G Ex ib IIC Gb II 1 G Ex ia IIC Ga	PYR PT100...EX PYR PT100...EX_A	IECEx IBE 15.0026U IBExU16ATEX1026 U	
Pt-100 for winding, type NWT 50C	H. Heinz Messwiderstände	II 2 G Ex eb IIC Gb II 2 G Ex ib IIC Gb II 1 G Ex ia IIC Ga	PYR PT100LC3/4ZEX	IECEx IBE 15.0026U IBExU16ATEX1026 U	

Certificate without signatures shall not be valid.
This certificate, including the annex may only be reproduced in its entirety and without any change.

Component	Manufacturer	Marking	ABB standard number or drawing	ATEX / IECEx certificate	Notes
Pt-100 for winding, types PR-SPA-EX-***	Ephy-Mess GmbH	II 2G Ex e IIC Gb or 2G Ex eb IIC II 2D Ex ta IIIC Da II 2G Ex ia IIC Gb II 2D Ex ia IIIC Db -55°C≤Ta≤175°C	PYR PT100...EX...	IBExU 14 ATEX 1281 U IECEx IBE 14.0058 U	
Pt-100 for winding, types S102040...	Minco	II 2 G Ex e IIC Gb II 1 G Ex ia IIC Ga	PYR PT100...EX	IECEx DEK 12.0057 U KEMA 03 ATEX 2240 U	
Purge controller for Ex p machines, types 2XLC... and 5XLC...	Expo Technologies	Ex [px] II T6 Ex [py] II T6 Ex [pz] II T6 Ex [p] dem IIC T3 Ex [pxb] ia IIC T6 Gb Ex [pxb] ia IIC T95°C Db (Ta -60°C to +60°C)	ZPEXP__PP450_ ZPEXP__PP_	SIRA 01 ATEX 1295X IECEx SIR 07.0027X	
Reducer / Adaptor type 476	Hawke	II 2 G Ex e IIC Gb II 2 D Ex tb IIC Db IP66	MRP HAW-...	IECEx BAS 11.0037X Baseefa 11 ATEX 0067X	
Roxtec, Cable entry, Cabletransit devices type S... and S...S0...	Roxtec International AB	II 2G Ex e IIC Gb II 2D Ex tb IIIC Db	NLR RM...	IECEx NEM 12.0015U Nemko 12 ATEX 1279U	
Self-limiting parallel heating cable HSB 07-5803-..., Anticondensation heater	BARTEC Barlian Technic	Ex e IIC 200 °C (T2), T3, T4 Gb Ex tb IIIC T 200 °C, T 195°C, T 130 °C Db	None	KEMA 02 ATEX 2327 U IECEx KEM 07.0048U	
Anticondensation heater cable, installation, termination plug Plexo H-1S 27-59SK-VH70 001S	BARTEC Barlian Technic	Ex e IIC 200 °C (T2), T3, T4 Gb Ex tb IIIC T 200 °C, T 195°C, T 130 °C Db	None	IECEx KEM 09.0083 KEMA 08 ATEX0110	
Anticondensation heater cable, installation, Connection plug Plexo H-CN 27-59SH-VH7P 00CN	BARTEC Barlian Technic	Ex e IIC 200 °C (T2), T3, T4 Gb Ex tb IIIC T 200 °C, T 195°C, T 130 °C Db	None	IECEx KEM 09.0083 KEMA 08 ATEX0110	
Sleeve bearing oil sump heater, Heater type DH..A0... and DH..BO..., type DH_00... is excluded	Elmess	Ex d e IIB/IIC Gb or Ex db eb IIB/IIC Ex d IIB/IIC Gb or Ex db IIB/IIC Ex d e ib IIB/IIC Gb or Ex db eb ib IIB/IIC Ex d ib IIB/IIC Gb or Ex db ib IIB/IIC Ex tb IIIC Db or Ex tb IIIC Ex tb ib IIIC Db or Ex tb ib IIIC	RER G1/2E220PT1 RER G1/2E220PT2	IECEx IBE 14.0078U IBExU 13 ATEX 1155U	
Stopping plug, Components in relation with cables entries Type A, AD, B, R, E, U, M, BM, OB	CAPRI-CODEC SA	II 2GD EEx e II EEx d IIC	None	IECEX LCI 08.0035X LCIE 98 ATEX 0001U	
Stopping plug, type 387	Hawke	II 2 GD Ex e IIC Gb, Ex tb IIIC Db IP66	None	IECEx BAS 06.0029U Baseefa 06 ATEX 0118U	
Stopping plug, type progress...Ex	AGRO	II 2 G Ex e II II 2 D Ex tD A21 IP 68	None	PTB 02 ATEX 1125 IECEx SEV 12.0001 PTB 02 ATEX 1126 X IECEx SEV 12.0002X	
Stopping plug, types V-Ex 1.297.****.** or V-Ms-VMQ-Ex 1.199.****.**	Hummel AG	Ex e IIC Gb Ex ta IIIC Da	MRP PET-EX..., MRP MET-EX...	IECEx BVS 07.0021 DMT 03 ATEX E 049	
Surge voltage arrester for RTD's, type plugtrab	Phoenix Contact	II 1 G Ex ia IIC T4...T6 Ga II 1 D Ex ia IIIC T85°C...135°C Da	NYA PT4-EX	IECEx KEM 10.0063X KEMA 00ATEX1099 X	
Temperature transmitter, type 5335D...	PR-Electronics	Ex ia IIC T4-T6 Ga Ex ia IIIC T135°C-T80°C Da	PYL TM1EX HART	IECEx KEM 10.0083 KEMA 03ATEX1537X	
Temperature transmitter, type 644 H or 644 R	Rosemount	II 1 G Ex ia IIC T4 Ga	None	IECEx BAS 07.0053X Baseefa12ATEX0101X	
Temperature transmitter, type Model 248	Rosemount	II 1 G Ex ia IIC T5/T6 Ga	None	IECEx BAS 07.0086X Baseefa 03 ATEX 0030X	

Certificate without signatures shall not be valid.
This certificate, including the annex may only be reproduced in its entirety and without any change.

Component	Manufacturer	Marking	ABB standard number or drawing	ATEX / IECEx certificate	Notes
Temperature transmitter, type Model 248	Rosemount	II 3 G Ex nA IIC T5/T6 Gc	None	IECEx BAS 07.0087U IECEx BAS 07.0055 IECEx BAS 13.0029X Baseefa 13 ATEX 0045U BAS 00 ATEX 3145 BAS 13 ATEX 0045X	
Temperature transmitter, type Model 248, 644	Rosemount	Ex d IIC T6...T1 Gb; T6...T1:Ta = -50°C to +40°C; T5...T1: Ta = -50°C to +60°C Ex tb IIIC T130C Db Ta = -40°C to +70°C; IP66	None	IECEx FMG 12.0022X FM 12 ATEX 0065X	
Temperature transmitter, type YTA Series	Yokogawa	II 1 G Ex ia IIC T4/T5 Ga Ex ia IIC T4 ... T5 Ga Ex ic IIC T4 ... T5 Gc II 1 D Ex iaD	None	KEMA 06 ATEX 0191X IECEx KEM 09.0032X	
Termistor for winding, type B59155-M...	Farell	-	PYRE 150H PYRE 170H PYRE 110H PYRE 90H PYRE 120H PYRE 130H PYRE 145H PYRE 155H	Has to be connected to Ex i circuit or alternatively can be installed without Ex i circuit if tested acc. to IEC 60079-7:2015 § 6.1	
Termistor for winding, type N-OK/AK ESH...	Ephy-Mess GmbH	-	PYRE 150LC4 PYRE 170LC4 PYRE 130LC4 PYRE 155LC4	Has to be connected to Ex i circuit or alternatively can be installed without Ex i circuit if tested acc. to IEC 60079-7:2015 § 6.1	
Termistor for winding, type TS100646T...	Minco	-	PYRE 150LC4 PYRE 170LC4	Has to be connected to Ex i circuit or alternatively can be installed without Ex i circuit if tested acc. to IEC 60079-7:2015 § 6.1	
Thermocouple for antifriction bearing	SKS Group Oy	-	PYR TCAB-K PYR TCAB-T PYR TCAB-J PYR TCAB-E	Has to be connected to Ex i circuit	
Thermocouple for sleeve bearing and cooling air	SKS Group Oy	-	PYR TCSB-E PYR TCSB-K PYR TCSB-T PYR TCSB-J	Has to be connected to Ex i circuit	
Water leakage detector for air-to-water cooler, type KAS-40-A12-N-5m art. No. 400200	Rechner Industrie-elektronik	Ex ia IIC T1 - T6 Ga Ex ia IIIC T101°C Da additionally for type *AS-*0-***-***-***-StEX	OXA KAS40A12N-EX	DMT 03 ATEX E 048 IECEx BVS 07.0031	
Velocity transducer for vibration monitoring, type 330500...	Bently Nevada	II 3 G Ex nA IIC T4 Gc II 3 D Ex tc IIIC T130°C Dc II 1 G Ex ia IIC T4 Ga	PYM 330500EX	Ex nA IIC T4 Gc and Ex tc IIIC T130°C Dc: IECEx LCI 06.0002X, LCIE 04 ATEX 6041X Ex ia IIC T4 Ga: IECEx LCI 06.0003X, LCIE 04 ATEX 6042X	
Water flow meter, type H250	Krohne	Ex ia II C T6 Gb	None	IECEx TUR 13.0006X PTB 01 ATEX 2181	
Pre-start Ventilation System for Ex nA and Ex e machines, type *PV*	Expo Technologies	II 2 G Ex e IIC T5 Gb /ET version, II 2 G Ex e ia IIC T5 Gb Low ambient, II 2 G Ex d e mb IIC T3 or T4 Gb Low ambient /ET version, II 2 G Ex d e ia mb IIC T3 or T4 Gb	ZPEXP__PSV_	IECEx SIR13.0030X Sira 13 ATEX 1083X	

Certificate without signatures shall not be valid.
This certificate, including the annex may only be reproduced in its entirety and without any change.

Component	Manufacturer	Marking	ABB standard number or drawing	ATEX / IECEx certificate	Notes
Pt-100 for winding, TSRC-series	Techno Controls	II 2 G Ex e IIC Gb	PYR PT100L...EX...	IECEx DNV 14.0014U DNV-2008-OSL-ATEX-40059U	
Pt-100 for winding fitted in winding end, TSRK-series	Techno Controls	II 2 G Ex e IIC Gb	PYR PT100...HA...4EX	IECEx DNV 14.0014U DNV-2008-OSL-ATEX-40059U	
Oil level monitor in self-lubricated sleeve bearings, Isolation switching amplifier type K*A*-SR*-Ex*.W.*	Pepperl + Fuchs	II (1) GD [Ex ia Ga] IIC, [Ex ia Da] IIIC [Ex ia Ma] I	None	IECEx PTB 11.0031 PTB 00 ATEX 2081	
Surge voltage arrester for RTD's, SD**xxx series	Measurement Technology Limited	Ex ia IIC T4 Ga	None	IECEx BAS 12.0003X BASEEFA 02 ATEX 0211X	
Pt-100 with connection head for sleeve bearing and cooling air temperature, Flameproof temperature sensors, Series AS8_	Minco	II 2 G Ex db eb IIC TX Gb	PYR PT100...D...EX, PYR 2PT100...D...EX	IECEx TRC 14.0017X TRAC 14 ATEX 0045X	
Pressure and temperature switches types 120, 121, 122, 820 and 822	United Electric Controls Company	II 2 G Ex db IIC T6 Gb II 2 D Ex tb IIIC T85°C Db IP66	None	IECEx UL 03.0001X DEMKO 09 ATEX 0815573X	
Temperature transmitter, type: STT 3000..., Model: STT 25...	Honeywell	II 1 G Ex ia IIC T4..T6 Ga Ex tD A21 IP6x T95°C Ex d IIC T5	None	IECEx LCI 08.0033X LCIE 02 ATEX 6134 X	
Main terminal boxes, types DA..._EX and DAXX...EX...	ABB Oy	II 2G Ex e IIC Gb II 3G Ex nA IIC Gc II 2D Ex tb IIIC Db	DA..._EX and DAXX...EX...	IECEx VTT 11.0003U VTT 11 ATEX 025U VTT 11 ATEX 026U	
Main terminal boxes, types E1LISE and E1LISR	ABB S.p.A.	II 2G Ex e IIC Gb II 2D Ex tb IIIC Db	E1LISE and E1LISR	IECEx CES 13.0020U CESI 03 ATEX 155U	
Main terminal boxes, types E1.SGR and E1.SPR	ABB S.p.A.	II 2G Ex e IIC Gb II 2D Ex tb IIIC Db	E1.SGR and E1.SPR	IECEx CES 14.0007U CESI 03 ATEX 154U	
Termistor for winding, type N-OK/AK ESH...	Ephy-Mess GmbH	II 2G Ex e IIC Gb or 2G Ex eb IIC II 2D Ex ta IIIC Da II 2G Ex ia IIC Gb II 2D Ex ia IIIC Db -55°C≤Ta≤175°C	PYRE 150LC4EX PYRE 170LC4EX PYRE 130LC4EX PYRE 155LC4EX	IBExU 14 ATEX 1281 U IECEx IBE 14.0058 U	
Surge suppression device type HAW569-CB2C	Endress+Hauser Wetzer GmbH	Ex d IIC T5 or T6 Gb	None	IECEx DEK 11.0013X DEKRA 11ATEX0034X	
Surge Arrester Type HAW569-DA2B	Endress+Hauser Wetzer GmbH	Ex ia [ia Ga] IIC T4 ... T6 Gb	None	IECEx DEK 11.0027X DEKRA 11ATEX0079X	
Auxiliary terminal box, stainless steel, Type: TNBCD	Bartec Technor	Ex d IIB T4 Gb, Ex d [ia Ga] [ib Gb] [op is Ga] IIB T6-T4 Gb Ex t [ia Da] [ib Db] IIIB T85°C – T135°C Db	None	IECEx TUN 12.0014X DNV-2003-OSL-ATEX-0136	
Drain plug, type 781D	CMP Products Limited	II 2G Ex d IIC Gb 1D Ex ta IIIC Da	None	IECEx SIR 10.0149U SIRA 10 ATEX 1307U	
Fan motors, types M3AA_	ABB	Ex nA IIB/IIC T3 Gc Ex tb IIIB/IIIC T125°C Db or Ex tc IIIB/IIIC T125°C Dc	None	IECEx VTT 13.0017X NEMKO 04 ATEX 3449	
Pt-100 for sleeve bearing and cooling air, types 65, 68, 78, 85, 183, 185 and 1067	Rosemount	Ex d IIC T6...T1 Gb, T6(-50 °C ≤ Ta ≤ +40 °C), T5...T1 (-50 °C ≤ Ta ≤ +60 °C) Ex tb IIIC T130C Db Ta=-40C to +70C, IP66	None	IECEx FMG 12.0022X FM 12 ATEX 0065X	
Pt-100 for sleeve bearing and cooling air, type TS...	ABB Automation Products GmbH	Ex ia IIC T6 Ga, Ex ib IIC T6, Ex ib IIC T6 Ga/Gb	None	IECEx PTB 11.0111X PTB 01 ATEX 2200 X	
Pt-100 for sleeve bearing and cooling air, type TS... Temperature sensors TSP..., Measuring inserts TSA..., Temperature transmitter TTF3	ABB Automation Products GmbH	Ex d IIIC T1 - T6 Ga/Gb	None	IECEx PTB 12.0039	
NAMUR Inductive proximity sensors - serie Ex IS M**b *ABBAB N 1GD*, _Speed switch	STEUTE SCHALTGERÄTE GmbH & Co. KG	Ex ia IIB/IIC T6 Ga Ex ia IIIC T85°C Da IP66/IP67/IP68	None	IECEx IMQ 14.0001X IMQ 14 ATEX 001	

Certificate without signatures shall not be valid.
This certificate, including the annex may only be reproduced in its entirety and without any change.

Component	Manufacturer	Marking	ABB standard number or drawing	ATEX / IECEx certificate	Notes
Auxiliary terminal box, types 1058..., 1059... and 1060..., equipped	Tranberg	Ex d e m ia/ib op pr IIC T6/T5/T4 Gb II 2 G Ex d e IIC T4/T5/T6 Gb II 2 G Ex eb T4/T5/T6 IIC II 2 G Ex e mb IIC T4/T5/T6 Gb	None	IECEx PRE 14.0001 Presafe 14 ATEX 4124	
Anticondensation heater, FX range of Enclosure Heaters, FXB225, FXB325, FXH225, FXH90, FXS	EXHEAT Limited	II 2 G Ex db IIC T4...T3 Gb II 2 D Ex tb IIIC T135°C...T200°C Db	REX 50, REX 80 and REX 200	IECEx ULD 16.0002X DEMKO 16 ATEX 1667X	
Pt-100 for sleeve bearing and cooling air, types 65 and 185	Rosemount	Ex db IIC T6...T1 Gb; T6...T1:Ta = -50°C to +40°C; T5...T1: Ta = -50°C to +60°C Ex tb III C T130C Db Ta = -40°C to +70°C; IP66	None	IECEx FMG 12.0022X	
Seismic transmitter, Types 190501, 330400, 330425, 330500, 330525	Bently Nevada	Ex ia IIC T4 Ga II 1 G Ex ia IIC T4 Ga	None	IECEx LCI 06.0003X LCIE 07 ATEX 6101 X	
Seismic transmitter, Types 190501, 330400, 330425, 330500, 330525	Bently Nevada	Ex nA IIC T4 Gc II 3 G Ex nA IIC T4 Gc Ex tc III C T130°C Dc	None	IECEx LCI 06.0002X LCIE 07 ATEX 6102 X	
Lockout swicth, type 07-3511-*, 07-3512-*, 07-3513-*,07-3514-*,07-3515-*, 07-3516-*	BARTEC GmbH	Ex db eb IIC T6 Gb or Ex db eb ia IIC T6 Gb Ex tb IIIC T80°C Db II 2 G D Ex d e IIC T6 Gb II 2 G D Ex d e ia IIC T6 Gb Ex tb IIIC T80°C Db	None	IECEx CML 14.0029X CML 14 ATEX 3073X	
Pressure switch, Series 1950G	Dwyer Instruments Inc	Ex d IIB+H_2 T6 Gb II2G Ex d IIB+H2 T6 Gb	None	IECEx DEK 11.0092X KEMA 03 ATEX 2402X	1
Pulse Encoder, type EN 42...	Dynapar Corporation	II 2G D Ex ia mb e IIC T4 Gb Ex tb IIIC T119°C Db	None	IECEx SIR 15.0051X SIRA 09ATEX5172X	
pulse encoder, type ISD 37... Optical Encoder Types 2222, 7272, 7273, 2222R, 7272R, 7273R and 4469	Dynapar Corporation	Ex ia IIB T4 Ga	None	IECEx SIR 15.0107X SIRA 03ATEX2170X	1
Pulse Encoder, type ISA 647_, ISA 648_, IHA 647_ or IHA 648_	Leine & Linde	Ex db IIC T6...T4 Ex tb IIIC T85°C	None	IECEx SP 15.0001X SP 15 ATEX 3649X	
Pt-100 for sleeve bearing and cooling air, type TS...	ABB Automation Products GmbH	Ex d IIIC T1 - T6 Ga/Gb	None	IECEx PTB 12.0039	
Cylindrical inductive sensors types NC... and NJ...	Pepperl & Fuchs	II 1 G Ex ia IIC T6 Ga II 2 G Ex ia IIC T6 Gb	None	IECEx PTB 11.0037X PTB 00 ATEX 2048X	
Water leakage detector for air-to-water cooler, type 1003, KSR	KSR Heinrich Kübler AG	II 1/2 G Ex c ia IIC T3...T6 Ga/Gb II 2 G Ex c d IIC T4...T6 Gb	OXA FLOAT 2-EX	SEV 11 ATEX 0188	
Auxiliary terminal box, 3300 XL Proximitor Housing, type 330181 -...	Bently Nevada	II 3 G EEx nA II T4/T5 Class I Div. 2, Groups A,B,C,D	None	BAS 99 ATEX 3102	
Flow switch, OXV PLD...	Officine Orobiche S.p.A.	II 1/2 G Ex d IIC T6, T5 Ga/Gb II 1/2 G Ex d/ib IIC T6, T5 Ga/Gb II 2 G Ex d IIC T6, T5 Gb II 1/2 D Ex ta/tb IIIC T85°C, T100°C Da/Db	OXV PLD-Ex	CESI 02 ATEX 126	
Inductive proximity switch, Speed switch, Namur Proximity Switches Types 08317 32... and 08318 32...	Pulsotronic	II 1 GD EEx ia IIC T6 T 85°C	None	KEMA 03 ATEX 1495X	
Measuring transducer, type TH 02-Ex and TH 202-Ex	ABB Automation Products GmbH	II 2 G EEx [ia] ib IIC T6	None	PTB 99 ATEX 2139 X	
Motion Guard, greese batchbox, Type 05-0078-...	Bartec Componenten and Systeme GmbH	II 2 G EEx d IIC T6	None	IBExU 02 ATEX 1065 X	

Certificate without signatures shall not be valid.
This certificate, including the annex may only be reproduced in its entirety and without any change.

Component	Manufacturer	Marking	ABB standard number or drawing	ATEX / IECEx certificate	Notes
Proximity transducer system for sleeve bearings, Amplifier, Driver: AD8/50 +DIN	Sensonics	II 1G EEx ia IIC T4	PXM XYKPA5-ABB	TRL 03 ATEX 21041X	
Proximity transducer system for sleeve bearings, Extension cable: AEXC/4.0AO	Sensonics	II 1G EEx ia IIC T4	PXM XYKPC4-ABB	TRL 03 ATEX 21041X	
Proximity transducer system for sleeve bearings, Extension cable: AEXC/4.0UO	Sensonics	II 1G EEx ia IIC T4	PXM XYKPCU4-ABB	TRL 03 ATEX 21041X	
Proximity transducer system for sleeve bearings, Probe: AECP04/1.0A210	Sensonics	II 1G EEx ia IIC T4	PXM XYKPP1-ABB	TRL 03 ATEX 21041X	
Proximity transducer system for sleeve bearings, Probe: AECP04/1.0U211 and probe holder	Sensonics	II 1G EEx ia IIC T4	PXM XYKPH1-ABB	TRL 03 ATEX 21041X Probe holder box: BAS 98 ATEX 3089U	
Proximity transducer system for sleeve bearings, Probe: AECP04/5.0A010	Sensonics	II 1G EEx ia IIC T4	PXM XYKPP5-ABB	TRL 03 ATEX 21041X	
Water leakage detector for air-to-water cooler, type Series EP type C, S, D	Officine Orobiche S.p.A.	II 1/2 G Ex d IIC T6, T5 Ga/Gb II 1/2 G Ex d/ib IIC T6, T5 Ga/Gb II 2 G Ex d IIC T6, T5 Gb II 1/2 D Ex ta/tb IIIC T85°C, T100°C Da/Db	OXA FLOAT 3-EX-...	CESI 02 ATEX 126	
Velocity transducer for vibration monitoring, type 107770...	Bently Nevada	II 3 G EEx nL IIC T4 II 1 G EEx ia IIC T4	PYM 107770EX	LCIE 04 ATEX 6041X and LCIE 04 ATEX 6042X	
Vibration sensor, type MTN/1107ICM8	Monitran	II 1 G EEx ia IIB T4	None	BAS 02 ATEX 1057	
Fan motors, types M3HP 80-400	ABB	II 2 G Ex e IIC T3 Gb Ex tb IIIC T85°C...T150°C Db	None	LCIE 06 ATEX 6047 LCIE 06 ATEX 6048 LCIE 06 ATEX 6049 LCIE 09 ATEX 3022 LCIE 09 ATEX 3023 LCIE 01 ATEX 6022 LCIE 01 ATEX 6023 LCIE 01 ATEX 6024 LCIE 02 ATEX 6071 LCIE 02 ATEX 6072 LCIE 03 ATEX 6022 LCIE 04 ATEX 6013	
Auxiliary terminal box, types GHG 74..., 73..., 72... and 44...	CEAG Sicherheitstechnik GmbH, Cooper Crouse Hinds	II 2 G Ex d e ia/ib m [ia/ib] IIC T4-T6 II 2 D Ex tD A21 IP66 T 80°C, T 95°C	None	PTB 99 ATEX 1044	
Pt-100 for sleeve bearing and cooling air, types 65 and 185	Rosemount	Ex ia IIC T6	None	IBEx 03 ATEX 1066X	
Water leakage detector for air-to-water cooler, Magnetic Float Switch, Level transmitter AF-ADF and AVK-ADF, Level regulator AL-ADF	Kubler France	II 2 G Ex d IIC T6 Gb II 2 D Ex tb IIIC T80C Db Ex d IIC T6 Ex tD A21 IP65 T80 °C -40 °C ≤ ta ≤ +55 °C	OXA FLOAT 4-EX	TÜV 13 ATEX 7399 X IECEx TUR 09.0002X	

Notes:

1 Not suitable for gas group IIC.